

<u>Home</u>

Products

Support

Industriesoducts / Regulators, Monit... / Monitoring / Fuel Drip Bunker ... / FG-K1-130-KW

Fuel Drip Bunker Samplers

wRardtt#вБуG-K1-130-KW



Parker bunker samplers are designed to provide a representative sample of the entire fuel delivery. Manufactured from stainless steel.

View Series Page 😑 Share / Email 📌 Print 🖨

Technical Specifications

Brand: Division:	Kittiwake Hydraulic & Industrial Process Filtration Division EMEA	Maximum Fluid Temperature:	75 °C, 167 °F	
Industry:	Marine	Flow Rate:	n/a	
Technology:	Filtration, Hydraulics	Sensing Method:	n/a	
Product Type:	Sampling System	Height:	748 mm	
Product Style:	Sample Capture Device	Width:	31.5 mm	
For Fluid Type:	Lube Oil Fuel	Outside Diameter:	328 mm	
Pipe Outside	250 mm	Port Size:	10 inch	
Diameter:		Port Type:	Pipe bore	
Operating Pressure:	40 bar, 580 psi	Materials of	Stainless Steel	
Operating	-50 to 75 °C, -58 to 167 °F	Construction:	Stainless Steel	
Temperature:		Body Material:	Stainless Steel	
Minimum Fluid	-50 °C, -58 °F	Seal Material:	Nitrile Rubber	
Temperature:		Specifications Met:	MARPOL regulations, IMO, ISO TR 13729 and Singapore Bunkering Procedure, ASTM D 4057, BS 3195, ISO 3170	
•				

▲ Safety Warning

Item Information

May 19th 2005 was the implementation date for IMO MARPOL Annex VI legislation, and ships the world over are using Parker Kittiwake's sampling equipment to adhere to these regulations. Parker Kittiwake supplies a full range of in-line bunker samplers and bunker sampling accessories, a complete range of sample bottles and consumables, plus a Germanischer LLoyd certified Bunker Sample Storage System.

Parker Kittiwake has a wide selection of bunker samplers and equipment ex-stock, ready for immediate delivery. There could not be a better time to ensure that you are IMO MARPOL compliant. Contact your local Parker representative for further details and to place your order.

Bunker samplers are designed to provide a representative sample of the entire fuel delivery. Manufactured from stainless steel, all products comply with ISO 3170, BS 3195, ASTM D 4057 and ISO TR 13729 standards, as well as the Singapore Bunkering Procedure.

Features and Benefits

· Lightweight and very easy to install

ded Parker^ae ex-stock UK accessories and consumables

Home CAD Drawings + Files

Products

SREPATEd Documents

Industries

Services



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS

 (\dots)



<u>Home</u>

- Products
- Support

Industries

Services

Solutions

Where to Buy