

) 🖫 🤉

Home

Products

Support

Industries oducts / Filters, Collecto... / Filter Parts and ... / Hydraulic Filter ... / Tank Accessories ... / FL69223

<u>Services</u>

Tank Accessories – Fluid Level / Temperature Gauges, Float and Capacitive Level Switches

Part #: FL69223





Parker offers a wide range of reservoir equipment and tank accessories designed to ensure the performance and reliability of hydraulic systems, including dual-purpose fluid / temperature gauges, capacitive level switches, and float level switches.

View Series Page

View Catalog(s)

✓

Share / Email → Print →

Technical Specifications

Type: Level Gauge Brand: Parker

Division: Hydraulic & Industrial Process Filtration Division EMEA

Length: 127 mm (5")

Port

Connection M12

Type:

Industry: Agrictulture, Construction, Oil and Gas, Marine, Mining,

Seal Material: Forestry

Deck and Mobile Cranes, Firefighting Equipment, Forwarders, Hydraulic Presses, Marine Steering Units, Power Packs, Waste

Application: Management, Dump and Fork Lift Trucks, Excavators,

Harvesters, Waste Balers, Reach Stackers, Wheeled Loaders,

Drilling Equipment, Industrial Power Units

Options: Incl. Thermometer
Technology: Hydraulics, Filtration
Product Type: Hydraulic Filter Accessories
Product Fluid Lovel (Tanasantus Cons

Series: Fluid Level / Temperature Gauges
For Fluid Type: Hydraulic Oil

For Fluid Type: Hydraulic Oi Operating Pressure: 1 bar

Operating
Temperature:
-30°C to +90 °C

Material:

Housing

Material:
Polyamide/Nylon/Polystyrene

⚠ Safety Warning

Item Information

Dual-Purpose Fluid Level / Temperature Gauges

Fluid level / temperature gauges utilize a universal fixing that is designed for front or rear tank mounting. The gauges are available in three cizes each with two-hole mounting at 76mm, 127mm and 254mm centers. After positioning the gauge, the bolts are simply tightened to provisecure seal. Square section seals minimize the likelihood of leakage while the two-point mounting system eliminates problems with tall distortion.

by the perature gauges feature a one-piece high-visibility lens for added security. The lens is molded in shatterproof, transparent sure accurate and clear oil level and temperature indication.



Home Features:

Provides with M10 or M12 bolt threads
Thermometer scale range: 30 to +90°C (86 to +194°F)
Support

Output

Description:

Industries Adjustable Float Level Switch – FL Series

Series comprises a range of vertically-mounted, single float level switches operating on the proven Reed switch and magnet principle. FL Series float switches can be tailored by the user for a particular application, by adjusting the length of the float switch tube. It is also possible for Solutions of select the switching configuration by inverting the float, giving either "open on rise" or "close on rise" operation. The unit is supplied partially assembled, with detailed instructions for the user to complete assembly to the specifications of the application and to install the unit. Where to Buy.

Features

- · Available in three lengths: 500mm, 1000mm, and 1500mm
- · Stem with the Reed switch and float already set in position
- · Supply voltage: 240 Vac maximum, 300 Vdc maximum
- Switching current: 0.5A
- · Mounting: 1" BSP threaded header
- · Gasket: 2mm thick sealing washer

Capacitive Liquid Level Switch - CLS46 Series

The CLS46 capacitive liquid level switch compliments the existing range of level measurement instrumentation supplied by Parker Hannifin. The switch is an active device designed to send an alarm signal if fluid falls below a pre-set level. The level switch has no moving parts, which minimizes its footprint and makes it suitable for applications where space and access inside vessels is limited. The CLS46 Series also features a built-in delay, making it an effective alternative to mechanically operated switches, which can often mis-trigger due to vibration and /or fluid turbulence.

Suitable for use with mineral oils typically used in engines or hydraulic actuators compatible with brass, PTFE and NBR.

Features:

- · Delay circuit prevents false alarms (10 seconds)
- · All-electric design eliminates moving components
- Supply current: 3.0mA
- Supply voltage: 7 40 Vdc

CAD Drawings + Files

- · Integrated test feature
- · Sealing: IP67
- Fluid temperature range: -40 to +130°C (-22 to +194°F)
- Ambient temperature range: -40 to +100°C (22 to +194°F)
- · Weight: 53 grams

- Didwings - Thes	•
Related Documents	+




Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

+ Compan	y Informatior
----------	---------------

- + Global Operations
- + Help & Support
- + Follow Us:





 $\not\sqsubseteq$ \bigcirc

—**⊋**arker

<u>Home</u>

Products

<u>Support</u>

Industries

<u>Services</u>

Solutions

Where to Buy