

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Regulators, Monit...](#) / [Flowmeters](#) / [High Pressure Mec...](#) / FM26232212

[Services](#)

High Pressure Mechanical Flowmeter - Flowline

[Solutions](#)

Part # FM26232212



The Flowline Series is a range of rugged inline mechanical flowmeters that provide visual indication of fluid flow in hydraulic systems. Capable of measuring flows ranging from 1 - 360 L/PM. Maximum allowable working pressure: 350 bar (5076 psi).

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Materials of Construction:	Stainless Steel, Brass	Flow Rate:	5 to 46 L/min
Body Material:	Nickel Plate, Brass	Port Size:	1/2 inch
Brand:	Parker	Port Type:	BSP Parallel Threads
Flow Rate:	5 to 46 l/min	Operating Temperature:	-20 to 90 °C
Division:	Hydraulic & Industrial Process Filtration Division EMEA	Sensing Method:	Variable Orifice Flow Meter
For Fluid Type:	Oil	Accuracy:	+/- 5% FSD
Industry:	Industrial & Chemical Processing	Specifications Met:	Pressure Directive
Housing Material:	Stainless Steel	Seal Material:	Fluoroelastomer
Technology:	Filtration	For Fluid Type:	Oil
Product Type:	Condition Monitor	Height:	41 mm
Product Style:	Flow Meter	Length:	165.5 mm
Operating Pressure:	5000 psi	Width:	41 mm
		Diameter:	46 mm

[Safety Warning](#)

Item Information

The Parker Flowline Series comprises a wide range of inline mechanical flow measurement devices that are designed for high-flow, high-pressure applications, including off-road mobile pump performance / industrial oil supply lines. The flowmeters are non-intrusive (i.e. do not obstruct flow) and are available with either a brass or stainless steel housing, making them suitable for use in harsh environments, where high-pressure and corrosive chemicals can damage conventional measurement devices.

Easiflow flowmeters are highly simplistic and versatile devices that utilize a variable-orifice aperture (i.e. variable area principle). The meters can work in any plane and feature an internal piston, which moves as flow rate increases, opening a larger area to pass flowing air, water or hydraulic oil. The design provides users with a direct visual indication of flow rate and serves as a highly reliable method of measuring flow in high-pressure fluid systems.

As an option, the meters can be equipped with a magnetically-operated reed switch that's capable of controlling valves and/or pumps, or

and provides signals in the event that flow exceeds or drops below a pre-determined level set by the user.



Multiple Flowline meters are available to meet the unique fluid flow requirements of customers' systems. Flow rates range from 0.2 - 360 L/min (0.05 - 95 GPM), with a maximum allowable working pressure of 350 bar (5000 psi). All Flowline devices are calibrated for both oil and water and feature accuracy and repeatability of +5% full scale deflection (FSD) and +1% FSD, respectively. The meters are relatively insensitive to viscosity changes.

[Home](#)
[Products](#)

Further information regarding compatibility with corrosive fluids can be provided by a Parker Filtration representative.

[Support](#)
[Markets:](#)
[Industries](#)

Oil and Gas / Pharmaceutical / Industrial / Process

[Services:](#)

•Rugged construction (brass or stainless steel) ensures reliable operation in harsh operating environments.

•Transparent glass body shroud construction allows users to quickly and easily determine flow rate in a system and/or line.

•Helps protect critical equipment from damage by ensuring that hydraulic fluid levels do not go above or below specified levels.

[Where to Buy](#)

[Features:](#)

- Capable of flows ranging from 0.2 - 360 L/min (.05 - 95 GPM)
- Operating temperature range (brass): -20 to +90°C (-4 to +194°F)
- Operating temperature range (316 stainless steel): -20 to +105°C (-4 to +221°F)
- Maximum allowable working pressure: 350 bar (5000 psi)
- Optional mechanically-operated reed switch
- Viscosity range: 10 to 200 cSt (oil)
- Calibrated for both oil and water

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor

CAD Drawings + Files +

Related Documents +



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44201926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
