



A comprehensive range of high quality indicators for mobile, industrial and marine applications. Maximum pressure 420 bar.

[View Series Page](#)[View Catalog\(s\)](#)[Share / Email](#)[Print](#)

Technical Specifications

Indicator Type:	Electronic 4 LED+M12 plug, PNP, Alarm:N.C.; Warning: N.O.	Connection Type:	SAE8
Indicator Pressure Setting:	5.0 bar	Maximum Operating Pressure:	420 bar
Seal Material:	Fluoroelastomer	Electrical Connection:	M12x1 -4 pin male connection
Housing Material:	Brass	Power Supply Voltage:	10 to 36VDC
		Options:	Temp. lockout 10°C

[Safety Warning](#)

Item Information

Ideal for giving accurate visual, electronic or electrical feedback of filter element condition, in order to facilitate effective maintenance and ensuring hydraulic systems, marine/mobile or industrial are protected from particulate contamination.

The DPI range of filter condition indicators are designed for use with Parker GMF and EPF filters. Whilst the FMU range are designed for use on a wide range of Parker filters and suitable for competitive interchange (consult Parker Filtration for details).

Product Features:

- Accurate visual, electronic or electrical filter condition feedback.
- Maximum pressure 420 bar.

Typical Applications

- Industrial equipment
- Mobile equipment
- Marine/offshore applications



+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
