

Filter Pressure and Vacuum Indicator - FMU and LPS Series

Part #: FMUG2FBRG02LBF



A comprehensive range of high quality indicators for mobile, industrial and marine applications.

[View Series Page](#)

[View Catalog\(s\)](#)

[Share / Email](#)

[Print](#)

Technical Specifications

Maximum Fluid Temperature:	60°C	Port Connection:	G $\frac{1}{8}$ "
Indicator Type:	Visual Pressure Gauge	Port Location:	Behind
Indicator Pressure Setting:	0 to 1.0 bar	Maximum Operating Pressure:	2.5 bar
Seal Material:	Nitrile	Electrical Connection:	No electrical connection
Housing Material:	Stainless steel	Power Supply Voltage:	Not applicable

[Safety Warning](#)

Item Information

Measuring critical system parameters is essential, FMU and LPS indicators enable reliable and continuous control of the filter in all applications.

Ideal for giving accurate electrical feedback of filter clogging condition in order to facilitate effective maintenance and ensuring hydraulic systems, marine/mobile or industrial are protected from particulate contamination.

Designed for use on a wide range of Parker filters and suitable for competitive interchange (consult Parker Filtration for details).

Product Features:

- Accurate visual, electronic or electrical filter condition feedback

Typical Applications

- Industrial equipment

- Mobile equipment
- Marine/offshore applications

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

