

Filter Differential Pressure Indicator - FMU and DPI Series

Part #: FMUX3HBMU12HS01



A comprehensive range of high quality indicators for mobile, industrial and marine applications. Maximum pressure 420 bar.

[View Series Page](#) [View Catalog\(s\)](#) [Share / Email](#) [Print](#) 

Technical Specifications

Indicator Type: Electronic, PNP, N.C., EX
Indicator Pressure Setting: 1.5 bar
Seal Material: Nitrile
Housing Material: Brass
Connection Type: 3/4-16 UNF-2A

Electrical Connection: Halogen free 10m cable
Maximum Operating Pressure: 420 bar
Power Supply Voltage: 10 to 36VDC
Options: Atex 94/9/EC: (Ex) II 2 GD Eex mII T6, with declaration of conformity

 [Safety Warning](#)

Item Information

Ideal for giving accurate visual, electronic or electrical feedback of filter element condition, in order to facilitate effective maintenance and ensuring hydraulic systems, marine/mobile or industrial are protected from particulate contamination.

The DPI range of filter condition indicators are designed for use with Parker GMF and EPF filters. Whilst the FMU range are designed for use on a wide range of Parker filters and suitable for competitive interchange (consult Parker Filtration for details).

Product Features:

- Accurate visual, electronic or electrical filter condition feedback.
- Maximum pressure 420 bar.

Typical Applications
• Industrial equipment

• Mobile equipment

• Marine/offshore applications

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

