= Parker		
<u>Home</u>		
Products		
Support		
Industries		
<u>Services</u>		
Solutions		
Where to Buy		

Home / Products / Filters, Collecto... / Filter Parts and ... / Hydraulic Filter ... / Replacement Eleme... / G04048Q

Replacement Elements - CN Series

Part #: G04048Q



High efficiency genuine replacement elements for Parker 15/40/80CN Series medium pressure hydraulic filters.

Ð

View Series Page 😑 Share / Email 🕈 Print 🖨

Technical Specifications

Division: For Use With: Brand: Length: Filter Element Type: Technology: Product Type:	Hydraulic and Industrial Process Filtration EMEA 40CN Parker Length 1 05Q Microglass Filtration Hydraulic Oil Filter	Application:	 Compressor Lube Oil Off-line Filter Loops Machine Tools (Automotive Standard) Hydrostatic Drive Charge Pumps Mobile Equipment Pilot Lines for Servo Controls Oil Patch Drilling Equipment Injection Molding Suitable for use with mineral and vegetable oils, and 	
Seal Material:	Nitrile	For Fluid Type:	some synthetic oils.	
Filter Type:	Medium Pressure Inline Filter	Flow Rate:	0 to 600 L/min	
Micron Rating: Product Series: Industry:	5 µm Replacement Elements - CN Series • Industrial Manufacturing Equipment - Automotive • Food & Beverage • Rubber & Plastics • Metals • Off-road Machinery • Agriculture • Construction • Forestry • Lawn & Turf • Mining • Materials Handling	Operating Pressure: Operating Temperature:	Maximum: 70 bar (1015 psi) Seal material Nitrile: -40°C to +100°C (-40°F to +212°F) Seal material Fluoroelastomer: -20°C to +120°C (-4°F to +248°F)-40 to +100°C	
A Safety Warning	- Military - Defence • Power Generation & Renewable Energy • Transportation - Rail - Trucks & Buses			

Item Information

The 15/40/80CN Series is a range of medium pressure filters offering an economical 'multipurpose' filter solution.

ffered with two types of element:

nt, making use of the Microglass media and in some sizes also available with ParGelWater removal media.

Parket Sales Sciences, UK environmentally friendly design without metal inner core. The Eco elements are used in versions of the CN filter with an Eco inner core fixed permanently inside the bowl of the filter. Having no metal content in the element reduces the overall weight with 50% and Results webterment of the second permanent in an environmentally friendly way by incineration, also lowering disposal costs. +44 (0)1926 317878

These elements are designed with the latest in filter media technology for first class system protection.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor. + Help & Support

CAD[®]Drawings + Files

Related Documents

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

╇

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS