

# High Pressure In-Line Filter - 18/28/38P Series

Part #: G04269



18/28/38P high pressure inline hydraulic oil filter series is a globally proven filter with optimised sizing covering flows up to 700 l/min and a pressure level up to 414 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Qty:

–  +

This  
auth  
or d

**Find a Distributor**

Where

**Division Contact**

Parker Sales Cor

Tachbrook Park  
Tachbrook Park  
Warwick  
United Kingdom  
CV34 6TU

**Phone:** +44 (0)

## Technical Specifications

Filter Element Type:  
Micron Rating:

20Q Microglass  
20 µm

Seal Material:  
Length:

[Safety Warning](#)

## Item Information

The 18/28/38P series of high pressure filters is designed to satisfy demanding applications in the global mobile and industrial markets. With metric filter series is truly a global design. This filter series has a wide range of high capacity and low initial differential pressure elements, offering excellent

Standard filters come complete with an industry proven spool type bypass valve. For more critical applications such as servo or proportional control maximum protection.

The low hysteresis differential pressure indicator fitted to this series is unrivalled in its performance.

Applications

- Mobile working hydraulics
- Mobile drive system



- Injection moulding
- Servo controls
- Die casting
- Machine tools

---

## CAD Drawings + Files

---

## Related Documents

---



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+441926317878)

---

+ Company Information

---

+ Global Operations

---

+ Help & Support

---

+ Follow Us :

---

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



