

Products

Support

Industries oducts / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure In-... / G04270

Services High Solutions Pressure In-Line Filter - 18/28/38P Series

WPharett#B06/04270



18/28/38P high pressure inline hydraulic oil filter series is a globally proven filter with optimised sizing covering flows up to 700 l/min and a pressure level up to 414 bar.

Ð

View Series Page 😑 Share / Email 🏞 Print 🖨

Technical Specifications

Filter Element Type: Micron Rating: 02Q Microglass 2 μm Seal Material: Length:

Fluoroelastomer 248 mm

Item Information

The 18/28/38P series of high pressure filters is designed to satisfy demanding applications in the global mobile and industrial markets. With metric mounting and optional ISO 6149 ports, this high pressure filter series is truly a global design. This filter series has a wide range of high capacity and low initial differential pressure elements, offering excellent protection to system components.

Standard filters come complete with an industry proven spool type bypass valve. For more critical applications such as servo or proportional controls, a no bypass, high strength element combination ensures maximum protection.

The low hysteresis differential pressure indicator fitted to this series is unrivalled in its performance.

Applications

- Mobile working hydraulics
- Mobile drive system
- Injection moulding
- Servo controls
- Die casting
- Machine tools

CAD Drawings + Files

Related Documents



 (\cdots)

PPackertSales Company UK

<u>Spsc.uktwebform@support.parker.com</u> +44 (0)1926 317878

Industries

structors any Information

Solutions Operations

Where to But port

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.



<u>Home</u>

Products

Support

Industries

Services

Solutions

Where to Buy

 \bigcirc