

a b 🗅

Home

Products

Support

Industries oducts / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure In-... / G04297

Services

High Pressure In-Line Filter - 18/28/38P Series

WPharet t#B@/04297





(+)

18/28/38P high pressure inline hydraulic oil filter series is a globally proven filter with optimised sizing covering flows up to 700 l/min and a pressure level up to 414 bar.

View Series Page

Share / Email

Print

Pr

Technical Specifications

Filter Element Type: 20QH High collapse Seal Material: Fluoroelastomer Micron Rating: 20 µm Length: 125 mm

▲ Safety Warning

Item Information

The 18/28/38P series of high pressure filters is designed to satisfy demanding applications in the global mobile and industrial markets. With metric mounting and optional ISO 6149 ports, this high pressure filter series is truly a global design. This filter series has a wide range of high capacity and low initial differential pressure elements, offering excellent protection to system components.

Standard filters come complete with an industry proven spool type bypass valve. For more critical applications such as servo or proportional controls, a no bypass, high strength element combination ensures maximum protection.

The low hysteresis differential pressure indicator fitted to this series is unrivalled in its performance.

Applications

- · Mobile working hydraulics
- Mobile drive system
- Injection moulding
- Servo controlsDie casting
- Machine tools

CAD Drawings + Files



Related Documents





Productsales Company UK

<u>Seppaktwebtorm@support.parker.com</u> +44 (0)1926 317878
<u>Industries</u>
Stervices Information
Sel Gritobras Operations
<u>Where</u> фо. В wyport
+ Follow Us:

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS





<u>Home</u>

Products

<u>Support</u>

Industries

<u>Services</u>

Solutions

Where to Buy