

l 🖫 🗇

Home

**Products** 

Support

Industries oducts / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure In-... / G04320

Services

# High Pressure In-Line Filter - 18/28/38P Series

WPharet t#B@/04320





18/28/38P high pressure inline hydraulic oil filter series is a globally proven filter with optimised sizing covering flows up to 700 l/min and a pressure level up to 414 bar.

View Series Page 

Share / Email 

Print 

Pr

## **Technical Specifications**

Filter Element Type: 10QH High collapse Seal Material: Fluoroelastomer Micron Rating: 10 µm Length: 248 mm

▲ Safety Warning

### **Item Information**

The 18/28/38P series of high pressure filters is designed to satisfy demanding applications in the global mobile and industrial markets. With metric mounting and optional ISO 6149 ports, this high pressure filter series is truly a global design. This filter series has a wide range of high capacity and low initial differential pressure elements, offering excellent protection to system components.

Standard filters come complete with an industry proven spool type bypass valve. For more critical applications such as servo or proportional controls, a no bypass, high strength element combination ensures maximum protection.

The low hysteresis differential pressure indicator fitted to this series is unrivalled in its performance.

#### Applications

- · Mobile working hydraulics
- Mobile drive system
- Injection moulding
- Servo controls
- · Die casting
- · Machine tools

## **CAD Drawings + Files**



## **Related Documents**





## Productsales Company UK

<u>Seppaktwebtorm@support.parker.com</u> +44 (0)1926 317878
<u>Industries</u>
Stervices Information
Sel Gritobras Operations
<u>Where</u> фо. В wyport
+ Follow Us:

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS





<u>Home</u>

**Products** 

<u>Support</u>

**Industries** 

<u>Services</u>

**Solutions** 

Where to Buy