Parker

Home

Products

Support

Industries Products / Filters, Collecto... / Replacement Filte... / Liquid Filter Ele... / Absolute Rated Pr... / G090102270E

Services

Solutions

Where to Buy

Absolute Rated Pre and Final Filtration Liquid Filters - PLEATFLOW

Part # G090102270E

Absolute rated efficiency 99.98% from 1 to 75 micron, available in a comprehensive range of end cap configurations and continuous lengths up to 40".

View Series Page ☰   Share / Email ➦   Print 🖶

Technical Specifications   ▬

Length:	9.75" (247 mm)	End Cap Configuration:	Double open end
Micron Rating:	1 µm	Filter Material:	Glass fibre / Polyester
Seal Material:	EPDM	Cage Material:	Rigid net
End Cap Material:	Polypropylene		

⚠ Safety Warning

Item Information   ▬

The Pleatflow range of filter cartridges offer ideal solutionsfor the pre and final filtration of a wide variety of process liquids, providing long service life at minimal cost.

The 100% polypropylene hardware construction of the filter ensures minimum extractable levels with a range of industrial solvents and optimal integrity when used in physically demanding applications.

Pleatflow filter cartridge manufacturing utilises graded density medias in both glass fibre and polypropylene. The filter design provides broad chemical compatibility, consistent efficiency and superior service life.

With absolute rated filtration efficiency and high surface area, Pleatflow filter cartridges are a cost effective solution for both pre and final filtration.

Applications
Catalyst recovery / Reagent grade chemicals / Make-up and wash waters / Membrane prefiltration

Features
• Absolute rated efficiency 99.98% from 1 to 75 micron.

• Available in a comprehensive range of end cap configurations and continuous lengths up to 40"

• Continuous length with rigid cage and core

• High pleated surface area available in both PP and GF

Benefits

Home

Products

Support

Industries

Services

Solutions

Where to Buy

- Consistent absolute retention suitable for a wide range of clarification applications
- Simple retrofitting to existing systems and housings
- Provides high strength during operation
- High flow rates and low initial pressure losses

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files ＋

Related Documents ＋

＋ Company Information

＋ Global Operations

＋ Help & Support

＋ Follow Us :

Home

Products

Support

Industries

Services

Solutions

Where to Buy