

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Replacement Filte...](#) / [Liquid Filter Ele...](#) / [Absolute Rated Pr...](#) / G090502273N

[Services](#)

Absolute Rated Pre and Final Filtration Liquid Filters - PLEATFLOW

[Solutions](#)

Part # G090502273N



Absolute rated efficiency 99.98% from 1 to 75 micron, available in a comprehensive range of end cap configurations and continuous lengths up to 40".

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

End Cap Configuration:	Flat / 222	Filter Material:	Glass fibre / Polyester
Micron Rating:	5 µm	Cage Material:	Rigid net
Length:	9.75" (247 mm)	Seal Material:	Nitrile
End Cap Material:	Polypropylene		

[Safety Warning](#)

Item Information

The Pleatflow range of filter cartridges offer ideal solutions for the pre and final filtration of a wide variety of process liquids, providing long service life at minimal cost.

The 100% polypropylene hardware construction of the filter ensures minimum extractable levels with a range of industrial solvents and optimal integrity when used in physically demanding applications.

Pleatflow filter cartridge manufacturing utilises graded density medias in both glass fibre and polypropylene. The filter design provides broad chemical compatibility, consistent efficiency and superior service life.

With absolute rated filtration efficiency and high surface area, Pleatflow filter cartridges are a cost effective solution for both pre and final filtration.

Applications


Catalyst recovery / Reagent grade chemicals / Make-up and wash waters / Membrane prefiltration

Features

- Absolute rated efficiency 99.98% from 1 to 75 micron.
- Available in a comprehensive range of end cap configurations and continuous lengths up to 40"
- Continuous length with rigid cage and core
- High pleated surface area available in both PP and GF

Benefits

- Consistent absolute retention suitable for a wide range of clarification applications
- Simple retrofitting to existing systems and housings



Home

- Provides high strength during operation

Products

- High flow rates and low initial pressure losses

Support

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

Industries

CAD Drawings + Files



Services

Solutions

Related Documents



Where to Buy



Parker Sales Company UK

psc.uk.webform@support.parker.com
+44 (0)1926 317878

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
