

[Home](#)[Products](#)[Support](#)[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Replacement Filte...](#) / [Liquid Filter Ele...](#) / [Absolute Rated Pr...](#) / [G2099T5270S](#)[Services](#)[Solutions](#)[Part # BG2099T5270S](#)

Absolute rated efficiency 99.98% from 1 to 75 micron, available in a comprehensive range of end cap configurations and continuous lengths up to 40".

[View Series Page](#)  [Share / Email](#)  [Print](#) 

## Technical Specifications

Micron Rating:	100 µm	End Cap Configuration:	Double open end
Length:	20" (508 mm)	Filter Material:	Polypropylene
Seal Material:	Silicone	Cage Material:	Rigid net
End Cap Material:	Polypropylene		

 [Safety Warning](#)

## Item Information

The Pleatflow range of filter cartridges offer ideal solutions for the pre and final filtration of a wide variety of process liquids, providing long service life at minimal cost.

The 100% polypropylene hardware construction of the filter ensures minimum extractable levels with a range of industrial solvents and optimal integrity when used in physically demanding applications.

Pleatflow filter cartridge manufacturing utilises graded density medias in both glass fibre and polypropylene. The filter design provides broad chemical compatibility, consistent efficiency and superior service life.

With absolute rated filtration efficiency and high surface area, Pleatflow filter cartridges are a cost effective solution for both pre and final filtration.

### Applications


Catalyst recovery / Reagent grade chemicals / Make-up and wash waters / Membrane prefiltration

### Features

- Absolute rated efficiency 99.98% from 1 to 75 micron.
- Available in a comprehensive range of end cap configurations and continuous lengths up to 40"
- Continuous length with rigid cage and core
- High pleated surface area available in both PP and GF

### Benefits

- Consistent absolute retention suitable for a wide range of clarification applications
- Simple retrofitting to existing systems and housings



#### Home

- Provides high strength during operation

#### Products

- High flow rates and low initial pressure losses

#### Support

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

#### Industries

### CAD Drawings + Files



#### Services

#### Solutions

### Related Documents



#### Where to Buy



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

---