

Low Pressure In-Line Filter - GA Series

Part #: GA3XXXBP2BG161



The In-line GA series low pressure filters feature magnetic pre-filtration and a wide range of filter media. A light weight aluminium housing design, with maximum flow rate of 320 l/min and a maximum pressure of 30 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Flow Rate:	0 to 300 l/min	Indicator Pressure Setting:	1.2 bar
For Use With:	GA 2-230	Seal Material:	Nitrile
Filter Element Type:	040W Wiremesh	Bypass Valve Pressure Rating:	2 bar
Micron Rating:	40 µm	Connection Type:	G1½
Indicator Type:	Vis/Electr. on right side, left side plugged	Options:	With magnets

[Safety Warning](#)

Item Information

The GA Series utilizes an aluminium housing design and can be specified with Microglass, Ecoglass (Leif), Cellulose or Wire mesh filter media.

Supplied with magnetic pre-filtration, making it ideal for use in hydraulic and lubrication oil systems, that can contain high levels of iron and other ferrous contaminants.

GA filters make use of the In-to-Out filter principle, which means there is no possibility for contaminated oil to leak back into the system.

Available with optional Visual or Visual/Electronic differential pressure indicators. Maximum nominal flow 320 l/min and maximum working pressure 30 bar.

Applications:
• Gearboxes

- Bypass filtration
- Stone crushers
- Lube oil systems
- Metal cutting equipment

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Related Documents



Related Products



Medium Pressure
Inline Hydraulic Oil
Filter – iProtect®
GMF Series



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

