

**Industries** Products / Filters, Collecto... / Filter Assemblies... / Lubrication Oil F... / Low Pressure In-L... / GA405QLBE3EG201

**LOW**  
**Solutions**

Where to Buy A405QLBE3EG201



View Series Page  Share / Email  Print 

---

Flow Rate:	0 to 40 l/min	Indicator Type:	No indicator, ports plugged L+R
For Use With:	GA 1-30	Operating Temperature:	-40 / +100 °C
Mounting Type:	Inline	Indicator Pressure Setting:	No indicator
Pressure Rating:	30 bar	Seal Material:	Nitrile
Filter Element Type:	20Q Microglass	Bypass Valve Pressure Rating:	1.5 bar
Micron Rating:	20 µm	Connection Type:	G¾
Housing Material:	Aluminium	Options:	With magnets



\_\_\_\_\_

Applications:

- Gearboxes
- Bypass filtration
- Stone crushers
- Lube oil systems
- Metal cutting equipment

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor



[Home](#)  
**Related Documents**  
[Products](#)



**Related Products**

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)



Medium Pressure  
Inline Hydraulic Oil  
Filter – iProtect®  
GMF Series



Parker Sales Company UK

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING **YOUR** SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

---

