

Tank Top Return Line Hydraulic Oil Filter – iProtect® GLF Series

Part #: GLF2120QIBP2GG20MF



The Parker GLF Series is a tank top return line hydraulic oil filter designed for high flow and long life between element change-outs. Maximum allowable flow 1700 L/min (374 GPM). Maximum allowable operating pressure 10.3 bar (150 psi) static.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Options:	Magnet Column & Funnel	Operating Pressure:	10 bar, 150 psi
Filter Element Type:	20QI (Quantumfiber™)	Operating Temperature:	-40 to 110 °C, -40 to 230 °F
Connection Type:	G1-1/4 thread - Single Port	Mounting Type:	Tank Mounted
Flow Rate:	0 to 300 l/min	Specifications Met:	Degree of filtration determined by multipass test according to ISO 16889.
Brand:	Parker	Housing Material:	Aluminium
Division:	Hydraulic & Industrial Process Filtration Division EMEA	Bypass Valve Pressure Rating:	1.7 bar, 24.6 psi
Industry:	Industrial Manufacturing Equipment, Materials Handling, Marine, Oil & Gas, Forestry, Construction, Mining Municipal Service Equipment, Dump and Fork Lift trucks, Deck and Mobile Cranes, Hydraulic Power Units, Waste Management, Drilling Equipment, Hydraulic Presses, Wheeled Loaders, Reach Stackers, Waste Balers, Forwarders, Excavators, Harvesters	Micron Rating:	20 MICRON
Application:		Indicator Type:	None / Both Indicator Ports Plugged
Technology:	Filtration, Hydraulics	Seal Material:	Nitrile
Product Type:	Hydraulic Oil Filter	Length:	177 mm
Product Series:	GLF iProtect Series	Height:	294 mm
For Fluid Type:	Hydraulic Oil	Width:	165 mm

[Safety Warning](#)

Item Information

The Parker GLF Series Low Pressure Tank Top Return Line Hydraulic Oil Filter delivers efficient contamination control for hydraulic circuits required to operate in highly demanding environments. The filter is ideally suited for applications where high system reliability and minimal downtime are critical, including heavy equipment and machinery used in mining, construction, marine, forestry, material handling and agricultural operations.

The GLF Series features an innovative design that provides maximum filtration capacity and extended element life, while maintaining low pressure drop, even in cold start conditions. High-efficiency Quantumfiber™ glass media is available in ratings 2, 5, 10, and 20 micron. Optional magnetic prefiltration is available for added protection in environments where ferrous contaminants are present while the bypass is opened. Magnetic prefiltration also extends life by preventing ferrous materials from settling on the filter media.

The GLF Series Return Line Filter's unique inside-to-outside flow path minimizes contaminant exposure to the reservoir during element change-out. Other notable features include pressure gauge and switch ports for visual or electrical switch monitoring, which makes it easy for operators to determine when the element needs to be serviced. Additionally, the filter features a versatile two-port design for enhanced installation flexibility.

Standard available port connection range:

- Single G12 up to G24
- Dual G24
- Single R24 up to R48
- Dual R24 up to R48

The GLF Series Return Line Hydraulic Oil Filter is designed for use with patented GLF Series Replacement Elements.

Benefits:

- Prevents contamination and ingress of dirt, sand, dust, metal, etc. into hydraulic circuits.
- Lengthens time in between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life.
- Maximizes filtration capacity and element life, while maintaining low pressure drop, even under cold start conditions.
- Versatile two-port design provides enhanced installation flexibility, resulting in lower installed cost.
- Protected aftermarket to guarantee the use of genuine products to protect equipment/machinery.
- Provides OEM branding (labelling) opportunities.
- High efficiency Quantumfiber™ glass media increases particle capture and dirt holding capacity.

CAD Drawings + Files



Related Documents



Related Products



Parker Certified
Accumulator Service
Centers



Parker Sales Company UK

psc.uk.webform@support.parker.com

+44 (0)1926 317878

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)