

Low Pressure In-Line Filter - GS Series

Part #: GS620QBNFG241



The In-line GS Series is a range low pressure filters suitable for use in several lube oil-, fuel- and hydraulic oil filtration applications
Suitable for a max. flow 350 l/min and a max. pressure of 40 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Flow Rate:	0 to 300 l/min	Bypass Valve Pressure Rating:	1.6 bar
Filter Size:	GS6	Connection Type:	G1½
Filter Element Type:	20Q Microglass	Indicator Type:	No indicator block, ports plugged
Micron Rating:	20 µm	Indicator Pressure Setting:	No indicator
Seal Material:	Nitrile	Options:	With bypass and magnets

[Safety Warning](#)

Item Information

Items marked with an asterisk * in the drop-down menus are standard choices.

The In-line GS Series comes in three different housing sizes and with several media options allowing a wide range of applications.
The Cast iron housings makes the GS series also suitable for marine application.
Pre-filtration with magnets is available as well as several connection options.
Available with Visual, Electrical or Visual/Electronic differential pressure indicators.
Max. nominal flow 350 l/min. Max. working pressure 40 bar.

- Applications:
- Industrial gear box lube oil filter
 - Heavy fuel oil filter for diesel engines
 - Suction filter for fuel systems
 - Low pressure hydraulic oil filter

CAD Drawings + Files

Related Documents

Related Products





Medium Pressure
Inline Hydraulic Oil
Filter – iProtect®
GMF Series



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



