

Low Pressure In-Line Filter - GS Series

Part #: GS7035WVNXD807



The In-line GS Series is a range low pressure filters suitable for use in several lube oil-, fuel- and hydraulic oil filtration applications
Suitable for a max. flow 350 l/min and a max. pressure of 40 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Flow Rate:	0 to 500 l/min	Bypass Valve Pressure Rating:	No bypass
Filter Size:	GS7	Connection Type:	DN80-PN16 (max. 16 bar)
Filter Element Type:	035W Wiremesh	Indicator Type:	No indicator block, ports plugged
Micron Rating:	35 µm	Indicator Pressure Setting:	No indicator
Seal Material:	Fluorelastomer	Options:	Safety cover, no bypass, no magnets

[Safety Warning](#)

Item Information

Items marked with an asterisk * in the drop-down menus are standard choices.

The In-line GS Series comes in three different housing sizes and with several media options allowing a wide range of applications. The Cast iron housings makes the GS series also suitable for marine application. Pre-filtration with magnets is available as well as several connection options. Available with Visual, Electrical or Visual/Electronic differential pressure indicators. Max. nominal flow 350 l/min. Max. working pressure 40 bar.

Applications:

- Industrial gear box lube oil filter
- Heavy fuel oil filter for diesel engines



- Suction filter for fuel systems
- Low pressure hydraulic oil filter

CAD Drawings + Files



Related Documents



Related Products

Medium Pressure
Inline Hydraulic Oil
Filter – iProtect®
GMF Series



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



