Parker

Home

Products

Support

Industries

Services

Solutions

Where to Buy

Low Pressure In-Line Filter - GS Series

Part #:GS7060WBNFG241

The In-line GS Series is a range low pressure filters suitable for use in several lube oil-, fuel- and hydraulic oil filtration applications
Suitable for a max. flow 350 l/min and a max. pressure of 40 bar.

View Series Page ☰   Share / Email ➔   Print 🖶

Technical Specifications —

Flow Rate:	0 to 500 l/min	Bypass Valve Pressure Rating:	1.6 bar
Filter Size:	GS7	Connection Type:	G1½
Filter Element Type:	060W Wiremesh	Indicator Type:	No indicator block, ports plugged
Micron Rating:	60 µm	Indicator Pressure Setting:	No indicator
Seal Material:	Nitrile	Options:	With bypass and magnets

⚠ Safety Warning

Item Information —

Items marked with an asterisk * in the drop-down menus are standard choices.

The In-line GS Series comes in three different housing sizes and with several media options allowing a wide range of applications.
The Cast iron housings makes the GS series also suitable for marine application.
Pre-filtration with magnets is available as well as several connection options.
Available with Visual, Electrical or Visual/Electronic differential pressure indicators.
Max. nominal flow 350 l/min. Max. working pressure 40 bar.

Applications:
• Industrial gear box lube oil filter
• Heavy fuel oil filter for diesel engines
• Suction filter for fuel systems
• Low pressure hydraulic oil filter

CAD Drawings + Files +

Related Documents

Medium Pressure Inline Hydraulic Oil Filter – iProtect® GMF Series

Parker Sales Company UK

psc.uk.webform@support.parker.com
+44 (0)1926 317878

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

Home

Products

Support

Industries

Services

Solutions

Where to Buy