

Top-mounted Breathers and Filler Breathers - AB Series

Part #: H00153-057



The Parker AB Series comprises a broad range of top-mounted breathers and filler breathers. The filler breathers protect hydraulic systems from airborne particle ingress, while allowing sufficient airflow into and out of the fluid reservoir.

[View Series Page](#)
[View Catalog\(s\)](#)
[Share / Email](#)
[Print](#)

Technical Specifications

Pressure Relief Valve Type:	Un-Pressurised	Installation:	Tank hole mounted
Micron Rating:	40 µm	Outside Diameter:	84 mm
Strainer Type:	355 mm strainer	Product Type:	Filler Breather
Connection Type:	6 Hole Installation	Includes:	Locking lug
Housing Material:	Plated mild steel	Seal Material:	Cork gasket
Features:	Locking lug	Flow Rate:	450 l/min

[Safety Warning](#)

Item Information

Ingress of airborne contaminants into hydraulic systems can cause a number of costly issues, including increased wear on pumps and cylinders, decreased performance, shorter maintenance intervals, and added downtime.

The Parker AB Series comprises a full range of top-mounted breathers and filler breathers designed to prevent this by keeping out harmful contaminants and allowing the tank / fluid reservoir to effectively breath during equipment operation. Multiple configurations are available to meet the unique requirements of customers' hydraulic systems, including:

Filler Breathers - Glass-filled nylon or plated metal steel. Multiple installation available including single hole, three hole, or six hole installation. Flow rates up to 620 L/min (163 GPM).

Screw-on type Breathers - Glass-filled nylon or plated metal steel. Multiple connection types available. Flow rates up to 620 L/min (163 GPM). Dipsticks available with all options (two lengths and in packs of 10).

Lockable Fillers and Filler Breathers (metal) - Pressurized and unpressurized threaded types available. For added reservoir security and oil protection, certain metal filler breathers can be specified with a locking lug option.

AB Series breathers and filler breathers are ideally suited for equipment required to operate in environments laden with dirt and dust.

Benefits

- Prevents contamination and ingress of dirt, sand, dust, metal, etc. into hydraulic circuits, while allowing sufficient airflow into and out of the fluid reservoir
- Lengthens time in between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life

Features:

- Molded in non-corrodible, glass-filled nylon – strong and light
- Filler breathers available with single hole, six hole, and three hole installation
- Screw-on breather range – G1/2 and G3/4 options
- Compact range – G1/4, G3/8, R1/2 and R3/4 options
- Metal filler breathers – pressurized and unpressurized threaded type
- Flange mounting type options
- Lockable options for reservoir security and oil protection

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Related Documents



Related Products

Hydraulic Reservoir
Breather / Air Filter -
EAB Series



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :
