

<u>Home</u>

Products

Support

Industries oducts / Filters, Collecto... / Filter Parts and ... / Hydraulic Filter ... / Tank Accessories ... / H00361-055

Services Tank Accessories – Fluid Level / Temperature Gauges, Float and Capacitive Level Switches

Part #: H00361-055



Parker offers a wide range of reservoir equipment and tank accessories designed to ensure the performance and reliability of hydraulic systems, including dual-purpose fluid / temperature gauges, capacitive level switches, and float level switches.

View Series Page :≡	View Catalog(s) 🖸
Share / Email 🔿	Print 🖨

Technical Specifications

Brand: Type:	Parker Level Gauge	Options: Technology:	Excl. Thermometer, with 55mm bolts Hydraulics, Filtration
Length:	254 mm (10")	Product Type:	Hydraulic Silter Accessories
Division:		Product Type.	Hydraulic Filter Accessories
Port	Hydraulic & Industrial Process Filtration Division EMEA	Series:	Fluid Level / Temperature Gauges
Connection	M12	For Fluid Type:	Hydraulic Oil
Туре:		Operating	1.01
Industry:	Agrictulture, Construction, Oil and Gas, Marine, Mining, Forestry	Pressure:	1.0 bar
Seal Material:	Nitrile	Operating Temperature:	-20°C to +85 °C
Application:	Deck and Mobile Cranes, Firefighting Equipment, Forwarders, Hydraulic Presses, Marine Steering Units, Power Packs, Waste Management, Dump and Fork Lift Trucks, Excavators, Harvesters, Waste Balers, Reach Stackers, Wheeled Loaders, Drilling Equipment, Industrial Power Units	Housing Material:	Resilient nylon with plated metal guard
\land Safety Warning			

Item Information

Dual-Purpose Fluid Level / Temperature Gauges

Fluid level / temperature gauges utilize a universal fixing that is designed for front or rear tank mounting. The gauges are available in three sizes each with two-hole mounting at 76mm, 127mm and 254mm centers. After positioning the gauge, the bolts are simply tightened to provide a secure seal. Square section seals minimize the likelihood of leakage while the two-point mounting system eliminates problems with tank distortion.



 $D_{\rm and}$ (comperature gauges feature a one-piece high-visibility lens for added security. The lens is molded in shatterproof, transparent $D_{\rm and}$ (consume accurate and clear oil level and temperature indication.

 \bigcirc

Home Features:

Products • Thermometer scale range: 30 to +90°C (86 to +194°F) • Working temperature: -30 to +90°C (22 to +194°F) support

Industries Adjustable Float Level Switch – FL Series

Series comprises a range of vertically-mounted, single float level switches operating on the proven Reed switch and magnet principle. FL Series float switches can be tailored by the user for a particular application, by adjusting the length of the float switch tube. It is also possible for Solutions o select the switching configuration by inverting the float, giving either "open on rise" or "close on rise" operation. The unit is supplied partially assembled, with detailed instructions for the user to complete assembly to the specifications of the application and to install the unit. Where to Buy

Features:

Available in three lengths: 500mm, 1000mm, and 1500mm

- · Stem with the Reed switch and float already set in position
- Supply voltage: 240 Vac maximum, 300 Vdc maximum
- Switching current: 0.5A
- Mounting: 1" BSP threaded header
- · Gasket: 2mm thick sealing washer

Capacitive Liquid Level Switch - CLS46 Series

The CLS46 capacitive liquid level switch compliments the existing range of level measurement instrumentation supplied by Parker Hannifin. The switch is an active device designed to send an alarm signal if fluid falls below a pre-set level. The level switch has no moving parts, which minimizes its footprint and makes it suitable for applications where space and access inside vessels is limited. The CLS46 Series also features a built-in delay, making it an effective alternative to mechanically operated switches, which can often mis-trigger due to vibration and /or fluid turbulence.

Suitable for use with mineral oils typically used in engines or hydraulic actuators compatible with brass, PTFE and NBR.

Features:

- Delay circuit prevents false alarms (10 seconds)
- All-electric design eliminates moving components
- Supply current: 3.0mA
- Supply voltage: 7 40 Vdc
- Integrated test feature
- Sealing: IP67
- Fluid temperature range: -40 to +130°C (-22 to +194°F)
- Ambient temperature range: -40 to +100°C (22 to +194°F)
- Weight: 53 grams

CAD Drawings + Files

Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.



<u>Home</u>

Products

Support

Industries

Services

Solutions

Where to Buy