

Replacement Elements - HF2/HF3/HF4

Part #: HF21H5VQ



These filter elements offer contamination protection for hydraulic systems ranging in use from standard power units to complex automotive systems.

[View Series Page](#)[View Catalog\(s\)](#)[Share / Email](#)[Print](#)

Technical Specifications

Micron Rating:	5 Micron Absolute	Media Material:	Multilayered microglass with epoxy coated mesh support
Filter Element Type:	HF2 Cartridge	Seal Material:	Fluorocarbon
Options:	High Collapse	Product Style:	Hydraulic Filter
Length:	Single	Product Type:	Hydraulic Filter Element

[Safety Warning](#)

Item Information

Designed to meet the very specialized requirements of the automotive industry, utilizing the same, high quality, high efficiency Microglass media as fitted to the standard filters. Microglass media available as 3, 5, 10 or 20 micron ($\beta_x \geq 200$). Media is supported both up and downstream and the whole assembly is bonded resulting in a 20 bar collapse rating. End caps and support tube are tin plated giving excellent corrosion protection.

HF2 4" and 8" Long. 3, 5, and 10 micron element with $\beta \geq 200$ and dual stage filtering media for up to 40% increased dirt holding capacity.
HF3 8" Long. 3, 5, and 10 micron element with $\beta \geq 200$ and dual stage filtering media for up to 40% increased dirt holding capacity.
HF4 10", 20", and 30" Long. 3, 5, and 10 micron with $\beta \geq 200$ and dual stage filtering media for up to 40% increased dirt holding capacity.

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44201926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

