

Home

Products

Support

Industries

Services

Solutions

Where to Buy

Home / Products / Filters, Collecto... / Replacement Engin... / Hydraulic Filter ... / Replacement Eleme... / HF41L3VQ

Replacement Elements - HF2/HF3/HF4

Part #: HF41L3VQ







These filter elements offer contamination protection for hydraulic systems ranging in use from standard power units to complex automotive systems.

View Series Page **:**≡ View Catalog(s)

Share / Email 🗪 Print =

Technical Specifications

Filter Element HF4 Cartridge

Type: Standard Collapse Options: Micron Rating: 3 Micron Absolute

Length:

Multilayered microglass with epoxy coated mesh Media Material:

support Seal Material: Fluorocarbon Product Style: Hydraulic Filter Product Type: Hydraulic Filter Element

▲ Safety Warning

Item Information

Designed to meet the very specialized requirements of the automotive industry, utilizing the same, high quality, high efficiency Microglass media as fitted to the standard filters. Microglass media available as 3, 5, 10 or 20 micron (ßx≥200). Media is supported both up and downstream and the whole assembly is bonded resulting in a 20 bar collapse rating. End caps and support tube are tin plated giving excellent corrosion protection.

HF2 4" and 8" Long. 3, 5, and 10 micron element with ß ≥ 200 and dual stage filtering media for up to 40% increased dirt holding capacity. HF3 8" Long. 3, 5, and 10 micron element with b ≥ 200 and dual stage filtering media for up to 40% increased dirt holding capacity. HF4 10", 20", and 30" Long. 3, 5, and 10 micron with β ≥ 200 and dual stage filtering media for up to 40% increased dirt holding capacity.

Related Documents



Parker Sales Company UK

<u>psc.uk.webform@support.parker.com</u> +44 (0)1926 317878

+ Company Information
+ Global Operations
+ Help & Support
+ Follow Us:

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS