

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [Mini High Pressur...](#) / [HPA.2625.100](#)

[Services](#)

Mini High Pressure Filter - HPA Series

[Solutions](#)

Part # HPA.2625.100



The HPA Series mini high pressure inline hydraulic oil filter is a small, robust filter concept with flow rates up to 45 l/min and pressure level up to 280 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Flow Rate:	0 to 35 l/min	Brand:	Parker
Options:	None	Technology:	Filtration
Connection Type:	G%	Product Type:	Hydraulic Filter
Filter Element Type:	N025 Cellulose Media	Filter Type:	Mini High Pressure Filter
Length:	Length 2	Product Series:	HPA Series
Seal Material:	Nitrile	Application:	<ul style="list-style-type: none"> • Lorry Mounted Cranes • Agricultural Equipment • Container Hhook Loaders
Micron Rating:	25 µm	Pressure Rating:	Maximum: 280 bar
Bypass Valve Pressure Rating:	5 bar	Housing Material:	Brass
Division:	Hydraulic and Industrial Process Filtration EMEA	Operating Temperature:	-30°C to +90°C

[Safety Warning](#)

Item Information

HPA Series mini high pressure filter are small and easy to install.

HPA is a robust solution to the low flow applications that larger filters are unable to effectively handle.

Made from high strength brass stampings and supplied with a wide range of media options. HPA Series mini pressure filters provide reliable, high efficiency protection.

Typical applications:

- Low Flow Servo Systems
- Pilot Lines
- Small Mobile Equipment
- Lubrication Systems
- High Pressure Water Systems

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.



+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
