

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [In-Tank Mounted F...](#) / [IN1120QBNEXX3](#)

[Services](#)

# In-Tank Mounted Filter - IN-AGB Series

[Solutions](#)

**Part #** IN1120QBNEXX3



The IN-AGB Series is a low cost, high performance in-tank mounted return line filter featuring a quick response bypass construction with low hysteresis and a high dirt-holding capacity.

[View Series Page](#)

[View Catalog\(s\)](#)

[Share / Email](#)

[Print](#)

## Technical Specifications

<p>Flow Capacity (l/min): 390</p> <p>Bypass Valve (bar): 1,5 *</p> <p>Filter Element: 20Q Microglass *</p> <p>Brand: Parker</p> <p>Flow Rate: 600 l/min</p> <p>Bypass Valve Pressure Rating: 1.5 bar</p> <p>Division: Hydraulic &amp; Industrial Process Filtration Division EMEA</p> <p>Filter Element Type: 20Q Microglass</p> <p>Industry: Industrial Manufacturing Equipment, Off-Road Machinery</p> <p>Micron Rating: 20 µm</p> <p>Application: Agricultural Machines, Articulated Dump Trucks, Forestry Equipment, Lubrication Systems, Excavators</p>	<p>Options: </p> <p>Technolc</p> <p>Seal Mate.</p> <p>Product Type: Hydraulic Filter</p> <p>Product Series: IN-AGB Series</p> <p>Height: 427 mm</p> <p>For Fluid Type: Hydraulic Oil</p> <p>Outside Diameter: 193 mm</p> <p>Operating Pressure: 0-34 bar, 0-500 psi</p> <p>Operating Temperature: -40 to +100 °C</p> <p>Mounting Type: Tank Mounted</p> <p>Specifications Met: Degree of filtration determined by multipass test according to ISO 16889.</p> <p>Indicator Type: No Indicator</p>	<p>Diffuser type T</p> <p>Hydraulics, Filtration</p> <p>Nitrile</p>
--	--	---

[Safety Warning](#)

## Item Information

The low-cost, high-performance return line IN-AGB filter features Q3 filter media, a bypass construction with low hysteresis, magnetic pre-filtration and a high dirt-holding capacity. The range is capable of handling flow rates from 30 l/min up to 2400 l/min. LEIF® elements are available for flow rates up to 1500 l/min, meeting the most stringent demands for environmentally-friendly filtration and offering protection against poor quality pirate elements.

### Features and Benefits

- The filter is integrated into the tank for a compact, low-cost design

• Production with low hysteresis for improved system protection.



• Magnetic pre-filtration removes ferrous particles, even during bypass conditions for improved fluid cleanliness levels and extended element life and a high dirt-holding capacity.

[Home](#)

[Products](#)

• Wide range of diffusers including airtight options.

[Support](#)

• Flow from inside to out ensuring all captured contamination is retained inside the element and no recontamination of the system during element change out can occur.

[Industries](#)

• Patented LEIF® elements safeguard filtration quality

[Services](#)

**CAD Drawings + Files**



[Solutions](#)

[Videos](#)

**Related Documents**



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ [Company Information](#)

+ [Global Operations](#)

+ [Help & Support](#)


+ [Follow Us :](#)

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

---

