

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [In-Tank Mounted F...](#) / IN1202QBNEXXX1

[Services](#)

In-Tank Mounted Filter - IN-AGB Series

[Solutions](#)

Part # **IN1202QBNEXXX1**



The IN-AGB Series is a low cost, high performance in-tank mounted return line filter featuring a quick response bypass construction with low hysteresis and a high dirt-holding capacity.

[View Series Page](#)

[View Catalog\(s\)](#)

[Share / Email](#)

[Print](#)

Technical Specifications

Brand:	Parker	Product T	Hydraulic Filter
Flow Rate:	250 l/min	Seal Mat	Nitrile
Bypass Valve		Height:	599 mm
Pressure Rating:	1.5 bar	Product Series:	IN-AGB Series
Division:	Hydraulic & Industrial Process Filtration Division EMEA	Outside Diameter:	150 mm
Filter Element Type:	O2Q Microglass	For Fluid Type:	Hydraulic Oil
Industry:	Industrial Manufacturing Equipment, Off-Road Machinery	Operating Pressure:	0-34 bar, 0-500 psi
Micron Rating:	2 µm	Operating Temperature:	-40 to +100 °C
Application:	Agricultural Machines, Articulated Dump Trucks, Forestry Equipment, Lubrication Systems, Excavators	Mounting Type:	Tank Mounted
Options:	No Diffuser	Specifications Met:	Degree of filtration determined by multipass test according to ISO 16889.
Technology:	Hydraulics, Filtration	Indicator Type:	No Indicator

[Safety Warning](#)

Item Information

The low-cost, high-performance return line IN-AGB filter features Q3 filter media, a bypass construction with low hysteresis, magnetic pre-filtration and a high dirt-holding capacity. The range is capable of handling flow rates from 30 l/min up to 2400 l/min. LEIF® elements are available for flow rates up to 1500 l/min, meeting the most stringent demands for environmentally-friendly filtration and offering protection against poor quality pirate elements.

Features and Benefits

- The filter is integrated into the tank for a compact, low-cost design
- Bypass construction with low hysteresis for improved system protection.

• Magnetic filtration removes ferrous particles, even during bypass conditions for improved fluid cleanliness levels and extended element life and holding capacity.



• Wide range of diffusers including airtight options.

[Home](#)

• Flow from inside to out ensuring all captured contamination is retained inside the element and no recontamination of the system during element change-out can occur.

[Products](#)

[Support](#)

• Patented LEIF® elements safeguard filtration quality

[Industries](#)

CAD Drawings + Files



[Services](#)

Related Documents



[Where to Buy](#)



Parker Sales Company UK

psc.uk.webform@support.parker.com

+44 (0)1926 317878

+ [Company Information](#)

+ [Global Operations](#)

+ [Help & Support](#)

+ [Follow Us :](#)

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

