

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [In-Tank Mounted F...](#) / IN1220QBNHXXX1

[Services](#)

In-Tank Mounted Filter - IN-AGB Series

[Solutions](#)

Part # **IN1220QBNHXXX1**



The IN-AGB Series is a low cost, high performance in-tank mounted return line filter featuring a quick response bypass construction with low hysteresis and a high dirt-holding capacity.

[View Series Page](#)

[View Catalog\(s\)](#)

[Share / Email](#)

[Print](#)

Technical Specifications

Brand:	Parker	Product Type:	Hydraulic Filter
Flow Rate:	600 l/min	Seal Material:	Nitrile
Bypass Valve Pressure Rating:	2.0 bar	Height:	599 mm
Division:	Hydraulic & Industrial Process Filtration Division EMEA	Product Series:	IN-AGB Series
Filter Element Type:	20Q Microglass	Outside Diameter:	150 mm
Industry:	Industrial Manufacturing Equipment, Off-Road Machinery	For Fluid Type:	Hydraulic Oil
Micron Rating:	20 µm	Operating Pressure:	0-34 bar, 0-500 psi
Application:	Agricultural Machines, Articulated Dump Trucks, Forestry Equipment, Lubrication Systems, Excavators	Operating Temperature:	-40 to +100 °C
Options:	No Diffuser	Mounting Type:	Tank Mounted
Technology:	Hydraulics, Filtration	Specifications Met:	Degree of filtration determined by multipass test according to ISO 16889.
		Indicator Type:	No Indicator

[Safety Warning](#)

Item Information

The low-cost, high-performance return line IN-AGB filter features Q3 filter media, a bypass construction with low hysteresis, magnetic pre-filtration and a high dirt-holding capacity. The range is capable of handling flow rates from 30 l/min up to 2400 l/min. LEIF® elements are available for flow rates up to 1500 l/min, meeting the most stringent demands for environmentally-friendly filtration and offering protection against poor quality pirate elements.

Features and Benefits

- The filter is integrated into the tank for a compact, low-cost design
- Bypass construction with low hysteresis for improved system protection.

Microfiltration removes ferrous particles, even during bypass conditions for improved fluid cleanliness levels and extended element life holding capacity.

Home [Wide range of diffusers including airtight options.](#)

Products [Flow from inside to out ensuring all captured contamination is retained inside the element and no recontamination of the system during element change out can occur.](#)

Support [Patented LEIF® elements safeguard filtration quality](#)

Industries [CAD Drawings + Files](#)

Services

Related Documents

Where to Buy



Parker Sales Company UK

psc.uk.webform@support.parker.com

+44 (0)1926 317878

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
