

<u>Home</u>

Products

Support

Industriesoducts / Filters, Collecto... / Replacement Filte... / Liquid Filter Ele... / Fulflo Honeycomb ... / M19R10S

## Services Fulflo Honeycomb Wound Filter Cartridges | Multi-purpose design with Solutions nominal 90% efficiency from 0.5-150 micron

Part #: M19R10S



Parker has been a leader in filter media innovation and performance since we first invented the Honeycomb<sup>™</sup> Filter Tube over 65 years ago. Parker has the world's largest manufacturing capacity for wound filter cartridges, offering superior quality.

View Series Page ☷	View Catalog(s) 🖸
Share / Email 🔿	Print 🖶

## **Technical Specifications**

Micron Rating (µm):	10	Specifications Met:	FDA
Industry:	Food and beverage	Flow Rate:	5 GPM per 10 inch
End Cap Finish:	No end treatment	End Cap Material:	No end cap
Core Cover Material:	No core cover	Filter Construction:	Polypropylene FDA grade
Brand:	domnick hunter	Packaging:	STANDARD PACKAGING
Function:	Clarification/Prefiltration/Polishing	End Cap Configuration:	DOE
Core Type:	316 Stainless steel	Seal Material:	No gasket
Media:	Polypropylene FDA grade	Length (inch):	10
Filter Construction:	Wound	Outside Diameter (inch):	2 7/16
Inside Diameter:	1 inch		
⚠ Safety Warning			

## **Item Information**

Parker has been a leader in filter media innovation and performance since we first invented the Honeycomb<sup>™</sup> Filter Tube over 65 years ago. Parker has the world's largest manufacturing capacity for wound filter cartridges, offering superior quality along with technical, engineering and marketing support.

Effective removal ratings at nominal 90% efficiency from 0.5µm to 150µm.

Features/Benefits

- · A broad range of media provide excellent compatibility with a variety of organic solvents, animal, petroleum and vegetable oils
- Optional core covers and end treatments assure fiber migration control
- Multiple length filter cartridges minimize change-out time, eliminate spacers and are available to fit competitive filter vessels
- FDA grade polypropylene (DOE only) filter cartridges certified to ANSI/ NSF61 standard for contact with drinking water components

<ul> <li>Action of winding geometry provides performance consistency extended center core option eliminates the need for cartridge guides in all competitive and Fulflo® multi-cartridge very extender is available for polypropylene cores</li> <li>Corton, polypropylene, nylon and polyester materials are FDA listed as acceptable for potable and edible liquid contact according to C "Oring/end cap options available</li> <li>ISO9001:2008 registered company Propuestions</li> <li>Oxidizing Agent Filtration</li> <li>Support Filtration</li> <li>Concentrated Filtration</li> <li>Potable Liquid Filtration</li> <li>Potable Liquid Filtration</li> <li>Solvitions Filtration</li> <li>Potable Liquid Filtration</li> <li>Pitter for Membranes</li> <li>Where tal Bojd Filtration</li> </ul>	ssels <sup>-</sup> R Title 21	
• Organic Acids & Solvent Filtration CAD Drawings + Files	+	
Related Documents		



## Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

 ENGINEERING YOUR SUCCESS.

 SITE MAP
 SAFETY
 PRIVACY POLICIES
 TERMS AND CONDITIONS



<u>Home</u>

- Products
- Support

Industries

Services

Solutions

Where to Buy