

Home

Products

Support

Industries

Services

Solutions

Where to Buy

Home / Products / Filters, Collecto... / Replacement Filte... / Liquid Filter Ele... / Fulflo Honeycomb ... / M19R30S

Fulflo Honeycomb Wound Filter Cartridges | Multi-purpose design with nominal 90% efficiency from 0.5-150 micron

Part #: M19R30S





(+)

Parker has been a leader in filter media innovation and performance since we first invented the Honeycomb™ Filter Tube over 65 years ago. Parker has the world's largest manufacturing capacity for wound filter cartridges, offering superior quality.

View Series Page **Ξ** View Catalog(s) **∠**

Share / Email 🕈 Print 🖶

Technical Specifications

Micron Rating (µm):

Industry: Food and beverage
End Cap Finish: No end treatment
Core Cover Material: No core cover
Brand: domnick hunter

Function: Clarification/Prefiltration/Polishing
Core Type: 316 Stainless steel

Media: Polypropylene FDA grade

Filter Construction: Wound Inside Diameter: 1 inch

⚠ Safety Warning

Specifications Met: FDA

Flow Rate: 5 GPM per 10 inch
End Cap Material: No end cap
Filter Construction: Polypropylene FDA grade

Packaging: STANDARD PACKAGING

End Cap Configuration:

Seal Material:

Length (inch):

Outside Diameter (inch):

DOE

No gasket

30

2 7/16

Item Information

Parker has been a leader in filter media innovation and performance since we first invented the Honeycomb™ Filter Tube over 65 years ago. Parker has the world's largest manufacturing capacity for wound filter cartridges, offering superior quality along with technical, engineering and marketing support.

Effective removal ratings at nominal 90% efficiency from 0.5µm to 150µm.

Features/Benefits

- · A broad range of media provide excellent compatibility with a variety of organic solvents, animal, petroleum and vegetable oils
- · Optional core covers and end treatments assure fiber migration control
- · Multiple length filter cartridges minimize change-out time, eliminate spacers and are available to fit competitive filter vessels
- FDA grade polypropylene (DOE only) filter cartridges certified to ANSI/ NSF61 standard for contact with drinking water components
- Continuous strand winding geometry provides performance consistency
- One-piece metal extended center core option eliminates the need for cartridge guides in all competitive and Fulflo® multi-cartridge vessels
- · A special snap-in extender is available for polypropylene cores
- · Cotton, polypropylene, nylon and polyester materials are FDA listed as acceptable for potable and edible liquid contact according to CFR Title 21
- O-ring/end cap options available
- ISO9001:2008 registered company

Applications

- · Oxidizing Agent Filtration
- Petroleum Oil Filtration
- Concentrated Filtration
- · Photo Solutions Filtration
- · Potable Liquid Filtration
- · Amines Filtration
- · Dilute Acids & Alkali Filtration
- Water Filtration
- · Prefilter for Membranes
- Mineral Acid Filtration
- · Organic Acids & Solvent Filtration

CAD Drawings + Files	+
Related Documents	+



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

+ Company	Information
-----------	-------------

+ Global Operations

+ Help & Support

+ Follow Us:

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS