

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [Low Pressure In-L...](#) / [MXA1210CBS3GG121](#)

[Services](#)

Low Pressure In-Line Spin-On Filter - Maxiflow Series

[Solutions](#)

Part # **MXA1210CBS3GG121**



The Maxiflow Series is a range of spin-on filters designed to provide low cost quality protection for hydraulic or lubrication systems.
Maximum pressure 10 bar. Maximum flow 360 l/min.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Brand:	Parker	Indicator Type:	Electrical 42V, NC, G $\frac{3}{4}$
Flow Rate:	0 to 60 l/min	Product Style:	Inline Spin-On Filter
Division:	Hydraulic & Industrial Process Filtration Division EMEA	Product Series:	Maxiflow
Bypass Valve:	1.7 bar	For Fluid Type:	Hydraulic Oils
Pressure Rating:	G $\frac{3}{4}$	Operating Pressure:	10 bar, 150 psi
Connection Type:	G $\frac{3}{4}$	Operating Temperature:	-30 to 100 °C, -22 to 212 °F
Industry:	Construction, Agriculture, Materials Handling	Flow Rate:	Up to 360 L/min
Filter Element Type:	10C Cellulose	Mounting Type:	Inline
Application:	Telescopic Handlers, Refuse Vehicles, Road Sweepers, Compactors, Industrial Power Units, Grass Cutters, Press Brakes	Housing Material:	Aluminium
Micron Rating:	10 μ m	Indicator Pressure Setting:	1.2 bar
Technology:	Filtration, Hydraulics	Materials of Construction:	Housing: Aluminium
Seal Material:	Nitrile	Options:	Standard
Product Type:	Hydraulic Filter		

[Safety Warning](#)

Item Information

Maxiflow full flow spin-on filters are designed to provide quality protection for hydraulic or lubrication systems. Rated at a maximum pressure of 10 bar at 360 l/min, Maxiflow filters cover a wide range of mobile and industrial applications.

Maxiflow filters are ideally suited to full flow and bypass circuit installations where the need for high quality filter media is recommended for effective protection of system components, improving system productivity and profitability. Optional indicators provide direct information as to when the spin-on canisters require replacement.

Features and Benefits

- Integrated indicator – Easy identification of element status

High quality filter medium – Long term protection against corrosion



Spin-on filters available for suction and return line filtration – Flexible product offering for standardisation of components

[Home](#)

High quality filter medium – suitable for fatigue load due to high frequent low fluctuation for extended element life time.

[Products](#)

CAD Drawings + Files



[Support](#)

[Industries](#)

Related Documents



[Services](#)

[Solutions](#)

Related Products

[Where to Buy](#)



Medium Pressure
Inline Hydraulic Oil
Filter – iProtect®
GMF Series



Parker Sales Company UK

psc.uk.webform@support.parker.com

+44 (0)1926 317878

+ [Company Information](#)

+ [Global Operations](#)

+ [Help & Support](#)

+ [Follow Us :](#)

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
