

**Products** 

Support

Industries oducts / Filters, Collecto... / Replacement Filte... / Liquid Filter Ele... / XTREAMPURE® XP Li... / PF000296

# TREAMPURE® XP Liquid Filter Cartridge

whart #BRF000296







XP-G1-4100E

View Series Page 

Share / Email 

Print 

Pr

50 PSID

35 PSID

### **Technical Specifications**

Nominal Inside Diameter:

Flow Direction: Inside-to-Outside

Maximum Pressure

Differential:

**Changeout Pressure** 

Differential:

Nominal Outside Diameter:

Division: Industrial Process Filtration Division

Model Number: ELMT XP-G1-4100E

Brand: PECO **Product Series:** XP-G1 Micron Rating: 10 40.5"

Cartridge Length: Nominal Outside Diameter: 6.3 Filter Construction: Pleated Nominal Inside Diameter: **Changeout Pressure** 

35 Differential:

**⚠** Safety Warning

Filter Material: Glass with Acrylic

Maximum Pressure

Differential:

SOE - Open top w/ handle outer chevron-style End Cap Configuration: seal, closed bottom

240 F

End Cap Material: Nylon

Flow Direction: Inside-to-Outside

Seal Material: **EPDM** Quantity per Box:

**Body Material:** Tin-Plated Steel

Product Type: Filter Cartridge Core Material: N/A

Industry: Oil and Gas

**Maximum Operating** 

Temperature: Technology: Filtration

pH Range: 3-9

#### **Item Information**

The XtreamPure®, Series XP, is a large 6" diameter cartridge designed to flow liquid from inside-to-outside. This design has several advantages. It allows for high flow rate capability within a single cartridge so fewer cartridges are needed compared to traditional 2.5" and 3" diameter designs. It keeps contaminants trapped within the cartridge, so the vessel remains clean. The cartridge includes a handled end cap with patented Chevron seal technology to provide an absolute sealing of the cartridge to the basket support. This means there is no need for tools when sealing making it a safe, user-friendly choice while also reducing maintenance time and money.

XtreamPure cartridges can be used in PECO brand Series 55HX and 55VX Filter Vessels or in competitors vessels with similar fit and function.

#### **INDUSTRIES**



- Large 6" diameter design yields higher flow rates and longer on-stream life than standard 2.5"

  Production

  The production of the producti
- Patented Chevron seal ensures complete sealing compared to a standard o-ring seal, especially when support plate or baskets are out of round Supports is are required to install or remove the cartridge and the integrated handled end cap provides a simple safe design to reduce change-out downtime

Industries outside flow ensures contaminant is captured inside the cartridge which provides cleaner and easier extraction during change-outs

#### **Services**

**APPLICATIONS** 

#### Solutions Water

Amine Systems

- <u>WRegeese Eluj</u>ds •Chemicals & Solvents
- •Offshore Pre-RO Water
- ·Hydrocarbons
- Condensate

## **CAD Drawings + Files Related Documents**



**Parker Sales Company UK** 

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us:

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.** 

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS



<u>Home</u>

**Products** 

<u>Support</u>

**Industries** 

<u>Services</u>

**Solutions** 

Where to Buy