

 $\blacksquare$  $\bigcirc$ 

**Products** 

Support

Industries oducts / Filters, Collecto... / Replacement Filte... / Natural Gas Filte... / PEACH® DYNASEP™ P... / PF000432

**Services** 

# PEACH® DYNASEP™ PCHG & EZ-PCHG Gas Filter-Separator Cartridge

#### WPharet t#BEVF000432







#### EZ-PCHG-343-SCW

View Series Page 

Share / Email 

Print 

Pr

## **Technical Specifications**

Micron Rating: 0.3 pH Range: 3-9 Maximum Pressure 30 PSID Differential: EZ-PCHG **Product Series:** Core Material: Tin-Plated Steel End Cap Material: Polyester Cartridge Length: 43"

Nominal Outside Diameter: 4.5"

SOE - Closed top w/ handle, open bottom w/ End Cap Configuration: external chevron seal

Buna-N

Seal Material: Maximum Operating 240 F Temperature:

Model Number: ELMT EZ-PCHG-343-SCW

Nominal Inside Diameter: 2.1" **Body Material:** N/A

**⚠** Safety Warning

Filter Material: Polyester Flow Direction: Outside-to-inside

**Changeout Pressure** 15 PSID Differential:

PEACH Depth Filter Construction:

Division: Industrial Process Filtration Division Brand: **PECO** Filter Construction: PEACH Depth

**Changeout Pressure** 15.0 Differential:

Flow Direction: Outside-to-inside

Quantity per Box: 4.0

Product Type: Filter Cartridge Industry: Oil and Gas

Application: Gas Particulate Filtration

Technology: Filtration

## **Item Information**

The PEACH® DYNASEP™ PCHG & EZ-PCHG Gas Filter-Separator cartridges are a great choice for removing deformable and shear sensitive contaminants from natural gas streams.

The PEACH® DYNASEP™ PCHG can be used in the PECO Series 75 and Series 85 vessels, as well as in several competitor filter-separator vessels. The synthetic construction allows for an environmentally friendly product and an excellent upgrade option to traditional fiberglass cartridges. The Series PCHG is made using the patented PEACH process which provides increased flow, high efficiency, and effective removal of contaminants. This equates to increased operational life, fewer change-outs, reduced maintenance, and reduced costs.

The PEACH DYNASEP® EZ-PCHG can be used in PECO Series 75HTL and 75VTL Titan PuraSep® vessels. The unique end cap design requires no tools, allowing for easy installation & removal during change-outs. The inclusion of EZ-Align® ensures a positive seal and prevents cartridge sagging. The unprecedented multidirectional, tortuous flow path creates a true gradient depth filter that increases residence time for contaminant removal while maintaining porosity and permeability through the media. PEACH cartridges have become a go-to filter used by consumers who have seen the benefits of longer on-stream service life between change-outs and improved effluent gas quality.



 $\bigcirc$ Ħ

# Home FEATURES/BENEFITS

Products
- PEACH® technology

- Support extraction device solid contaminant from a natural gas stream while also preparing liquid droplets to be coalesced by second stage mist extraction device
- Removes contaminants such as asphaltenes, coal fines, dirt, iron sulfides, molecular sieve dust, pipe scale, salt, sand, wear metals <u>Industries</u>

APPLICATIONS

#### Services te

Compressor & Turbine Suction

Solutions Towers (Inlet & Overhead)

• Custody Transfer Fuel Gas

#### Whoeve Dios Bilbyution

- · Gas Storage
- Gas Transmission
- Gas Treating & Dehydration
- · Landfill Gas
- M&R Stations
- · Plant Entrance Gas

# **CAD Drawings + Files Related Documents**



**Parker Sales Company UK** 

psc.uk.webform@support.parker.com +44 (0)1926 317878

+	Company	<b>Information</b>

- + Global Operations
- + Help & Support
- + Follow Us:

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS



 $\exists$   $\bigcirc$ 

<u>Home</u>

**Products** 

<u>Support</u>

**Industries** 

**Services** 

**Solutions** 

Where to Buy