



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

[Home](#) / [Products](#) / [Regulators, Monit...](#) / [Diagnostic Testin...](#) / [Pressure Gauges -...](#) / PGB0631040

Pressure Gauges - Reservoir Equipment

Part #: PGB0631040



Parker Pressure Gauges provide reliable visual indication of system pressure, having several pressure ranges up to 600 bar and available with multiple connection options.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Operating Pressure:	0-40 bar (0-580 psi)		
Division:	Hydraulic and Industrial Process Filtration EMEA	Materials of Construction:	Case: BS 304 S15 Stainless Steel
Brand:	Parker		Window: Acrylic
Port Size:	G1/4		Movement: Brass
Product Type:	Pressure Gauge	Connection Type:	Dial: White Aluminium
Diameter:	63 mm (2.5 inch)	Ingress Protection Rating:	Pointer: Black Aluminium
		Options:	Bottom
			IP 65
			Bourdon Tube: Phosphor bronze, C-type

[Safety Warning](#)

Item Information

Pressure gauges are used in several applications to give an instant visual indication of system pressure level.

Parker pressure gauges have a stainless steel casing and acrylic glass window. They are filled with 99,7% glycerine.

Features

- Temperature range up to 60°C.
- Accuracy down to 1.0% of full scale.
- IP Class 65.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.



Parker Sales Company UK

psc.uk.webform@support.parker.com

[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING **YOUR** SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

