

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [Tanktop Mounted R...](#) / PT4310QBG2GG201

[Services](#)

Tanktop Mounted Return Line Filter - PT Series

[Solutions](#)

Part # BPT4310QBG2GG201



The PT tank top mounted filter offers an economical solution for quality tank top mounted filtration. Maximum pressure 10 bar. Maximum flow 400 l/min.

[View Series Page](#)

[View Catalog\(s\)](#)

[Share / Email](#)

[Print](#)

Technical Specifications

Seal Material:	Nitrile *	Operating Temperature:	-20 / +100 °C
Bypass Valve Pressure Rating:	1,7 bar	Flow Capacity (l/min):	400 *
Mounting Type:	Tank Mounted	Indicator	Visual
Pressure Rating:	10 bar	Filter Element	10Q Microglass
Flow Rate:	400 L/min	Port Connection Type:	G1 1/4 *
Housing Material:	Aluminium	Options:	Without diffuser

[Safety Warning](#)

Item Information

Items marked with an asterisk * in the drop-down menus are standard choices.

The PT filter features an aluminium filter head and screw-in style filter elements. The element has an In to Out flow design that avoids re-contamination of the hydraulic system. Having a Parker design that protects the quality of filtration, the PT offers great value for money.

The PT Series filter is available in various sizes covering a flow rate up to 400 l/min. Using Microglass media in 2, 5, 10 and 20 microns it provides premium particle removal efficiency. The disposable filter cartridge is a single-piece construction, which incorporates the nylon cover and integral 1.7 bar bypass valve. The flow path is inside-out and the element requires no special tools for service.

With its unique design the filter element simply threads into a ported tank ring, which can be bolted to a metal reservoir. This concept assures minimal installation costs with the least space requirements for return line applications. This also offers the opportunity to use just the filter element as screw-in style element for co-polymer reservoirs.

Product Features:

- Compact tank top mounted return line filter.
- Filter element can be used for direct screw-in mounting with co-polymer reservoirs.
- Parker quality filter element.

- Prevents re-contamination of the system.
- up to 400 l/min at 10 bar working pressure.



- Typical Applications:
 - Lorry mounted cranes
 - Agricultural equipment
 - Grass cutting equipment
 - Container hook loaders

[CAD Drawings + Files](#) +

[Services](#)

[Related Documents](#) +

[Solutions](#)

[Where to Buy](#)



Parker Sales Company UK

psc.uk.webform@support.parker.com
+44 (0)1926 317878

+ [Company Information](#)

+ [Global Operations](#)

+ [Help & Support](#)

+ [Follow Us :](#)

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

