

# Tanktop Mounted Return Line Filter - PT Series

Part # PT4310QBS2GG204



The PT tank top mounted filter offers an economical solution for quality tank top mounted filtration. Maximum pressure 10 bar. Maximum flow 400 l/min.

[View Series Page](#)[View Catalog\(s\)](#)[Share / Email](#)[Print](#)

## Technical Specifications

Seal Material:	Nitrile *	Operating Temperature:	-20 / +100 °C
Bypass Valve Pressure Rating:	1,7 bar	Indicator <sup>†</sup>	Electrical 42V, NO, G1/8
Mounting Type:	Tank Mounted	Flow Cap (in):	400 *
Pressure Rating:	10 bar	Filter Elen	10Q Microglass
Flow Rate:	400 L/min	Port Connection Type:	G1 ¼ *
Housing Material:	Aluminium	Options:	With diffuser *

 [Safety Warning](#)

## Item Information

Items marked with an asterisk \* in the drop-down menus are standard choices.

The PT filter features an aluminium filter head and screw-in style filter elements. The element has an In to Out flow design that avoids re-contamination of the hydraulic system. Having a Parker design that protects the quality of filtration, the PT offers great value for money.

The PT Series filter is available in various sizes covering a flow rate up to 400 l/min. Using Microglass media in 2, 5, 10 and 20 microns it provides premium particle removal efficiency. The disposable filter cartridge is a single-piece construction, which incorporates the nylon cover and integral 1.7 bar bypass valve. The flow path is inside-out and the element requires no special tools for service.

With its unique design the filter element simply threads into a ported tank ring, which can be bolted to a metal reservoir. This concept assures minimal installation costs with the least space requirements for return line applications. This also offers the opportunity to use just the filter element as screw-in style element for co-polymer reservoirs.

Product Features:

- Compact tank top mounted return line filter.
- Filter element can be used for direct screw-in mounting with co-polymer reservoirs.
- Parker quality filter element.

- Prevents re-contamination of the system.
- Up to 400 l/min at 10 bar working pressure.



Typical Applications:

- Lorry mounted cranes
- Agricultural equipment
- Grass cutting equipment
- Container hook loaders

[Support](#)

[CAD Drawings + Files](#)

[Industries](#)

[Services](#)

[Related Documents](#)

[Solutions](#)

[Where to Buy](#)



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)

[+44 \(0\)1926 317878](tel:+44(0)1926317878)

[+ Company Information](#)

[+ Global Operations](#)

[+ Help & Support](#)

[+ Follow Us :](#)

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

---

