

Mini High Pressure Filter - HPA Series

Part #: S.380007



The HPA Series mini high pressure inline hydraulic oil filter is a small, robust filter concept with flow rates up to 45 l/min and pressure level up to 280 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Micron Rating:	40 µm	Brand:	Parker
Connection Type:	G¼	Technology:	Filtration
Length:	Length 1	Product Type:	Hydraulic Filter
Bypass Valve Pressure Rating:	No bypass	Filter Type:	Mini High Pressure Filter
Seal Material:	Nitrile	Product Series:	HPA Series
Options:	Stainless Steel Element	Application:	<ul style="list-style-type: none"> • Lorry Mounted Cranes • Agricultural Equipment • Container Hhook Loaders
Filter Element Type:	040 Wiremesh	Pressure Rating:	Maximum: 280 bar
Flow Rate:	0 to 24 l/min	Housing Material:	Brass
Division:	Hydraulic and Industrial Process Filtration EMEA	Operating Temperature:	-30°C to +90°C

[Safety Warning](#)

Item Information

HPA Series mini high pressure filter are small and easy to install.

HPA is a robust solution to the low flow applications that larger filters are unable to effectively handle.

Made from high strength brass stampings and supplied with a wide range of media options. HPA Series mini pressure filters provide reliable, high efficiency protection.

Typical applications:

- Low Flow Servo Systems
- Pilot Lines
- Small Mobile Equipment
- Lubrication Systems
- High Pressure Water Systems

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

