

Q



 \bigcirc

Home

Products

Support

Industries oducts / Filters, Collecto... / Filter Parts and ... / Hydraulic Filter ... / Top-mounted Breat... / SAB.1562.10

Services

Top-mounted Breathers and Filler Breathers - AB Series

WPharet t#BByAB.1562.10





(+)

The Parker AB Series comprises a broad range of topmounted breathers and filler breathers. The filler breathers protect hydraulic systems from airborne particle ingress, while allowing sufficient airflow into and out of the fluid reservoir.

View Series Page **□** View Catalog(s) **□**

Share / Email 🕈 Print 🖶

Technical Specifications

Valve Type:

Industry:

Agriculture, Construction, Oil and Gas, Marine, Mining,

Flow Rate: 430 l/min

Deck and Mobile Cranes, Firefighting Equipment, Forwarders, Hydraulic Presses, Marine Steering Units, Power Packs, Application: Waste Management, Dump and Fork Lift Trucks, Excavators,

Harvesters, Waste Balers, Reach Stackers, Wheeled Loaders,

Drilling Equipment, Industrial Power Units

Micron Rating: 10 μm

▲ Safety Warning

Technology: Filtration, Hydraulics

Srew-On

Air

Connection G3/4 male thread

Installation:

For Fluid Type:

Product Series: AB Series
Strainer Type: Without strainer

Includes: Operating -30 / +90

Temperature: -30 / +90
Outside 76 mm

Diameter: 70 min

Mounting Type: Tanktop

Seal Material: No seal

Filter Material: 10µ abs. PU-foam

Item Information

Ingress of airborne contaminants into hydraulic systems can cause a number of costly issues, including increased wear on pumps and cylinders, decreased performance, shorter maintenance intervals, and added downtime.

The Parker AB Series comprises a full range of top-mounted breathers and filler breathers designed to prevent this by keeping out harmful contaminants and allowing the tank / fluid reservoir to effectively breath during equipment operation.

Multiple configurations are available to meet the unique requirements of customers' hydraulic systems, including:

Glass-filled nylon or plated metal steel. Multiple installation available in which single hole, three hole, or six hole installation.

Screw-on type Breathers - Glass-filled nylon or plated metal steel. Multiple connection types available. Flow rates up to 620 L/min (163 GPM). Products

Lockable Fillers and Filler Breathers (metal) - Pressurized and unpressurized threaded types available. For added reservoir security and oil protection, certain metal filler breathers can be specified with a locking lug option.

Industries breathers and filler breathers are ideally suited for equipment required to operate in environments laden with dirt and dust.

Services:

• Prevents contamination and ingress of dirt, sand, dust, metal, etc. into hydraulic circuits, while allowing sufficient airflow into and out of the fluid Solutions

Where the between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life

Features:

- Molded in non-corrodible, glass-filled nylon strong and light
- Filler breathers available with single hole, six hole, and three hole installation
- Screw-on breather range G1/2 and G3/4 options
- · Compact range G1/4, G3/8, R1/2 and R3/4 options
- Metal filler breathers pressurized and unpressurized threaded type
- · Flange mounting type options
- · Lockable options for reservoir security and oil protection

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files	+
Related Documents	+



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

+ Company Information		

- + Global Operations
- + Help & Support
- + Follow Us:

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS



 \exists \bigcirc

<u>Home</u>

Products

<u>Support</u>

<u>Industries</u>

Services

Solutions

Where to Buy