

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Parts and ...](#) / [Hydraulic Filter ...](#) / [Suction Elements ...](#) / SE.75362410

[Services](#)

Suction Elements / Inbuilt Filters - SE Series

[Solutions](#)

Part # SE.75362410



The Parker SE Series comprises a range of suction elements / inbuilt tank filters. The elements are equipped with 125 micron rating abs steel wire mesh media and are capable of flows ranging from of 15 - 500 l/min (4 -132 gpm).

[View Series Page](#)

[View Catalog\(s\)](#)

[Share / Email](#)

[Print](#)

Technical Specifications

Bypass Valve Pressure Rating:	No Bypass		
Port Type:	2" NPT	Industry:	<ul style="list-style-type: none"> • Agriculture • Construction • Oil and Gas • Marine • Mining • Forestry • Deck and mobile cranes • Firefighting equipment • Forwarders • Hydraulic presses • Marine steering units • Power packs • Waste management, dump and fork lift trucks
Flow Rate:	180 l/min		
Length:	259.0 mm		
Outside Diameter:	86.0 mm		
Micron Rating:	125.0 UM		
Options:	None		
Mounting Type:	Tank Mounted	Application:	<ul style="list-style-type: none"> • Excavators • Harvesters • Waste balers • Reach stackers • Wheeled loaders • Drilling equipment • Industrial power units
Housing Material:	Nylon/Plated mild steel		
Operating Temperature:	-30 / +90 °C		
Division:	Hydraulic and Industrial Process Filtration		
	EMEA		
Brand:	Parker		
Technology:	Filtration		
Product Type:	Hydraulic Filter		

[Safety Warning](#)

Item Information

Parker SE Series suction elements / inbuilt reservoir filters are designed to prevent large objects (i.e., stones, deposits, sticks, etc.) from entering hydraulic system pumps, which can cause increased wear and tear to critical components, shorter maintenance intervals, and added downtime. The elements are designed for installation inside the reservoir / tank and are equipped with 125 micron rating abs steel wire mesh media, which provides maximum filtration efficiency and full fluid flow, thus ensuring reliable system performance.

Multiple flow capacities (15 - 500 L/min) and mounting threads (G½, G¾, G1, G1½, G2, G2½, G3) are available to meet the unique customers' systems. Suction elements with an integrated 0.17 bar bypass valve are also available as an option.

Typical applications for SE Series tank inbuilt filters include saw mills, agricultural machines, articulated dump trucks, forestry equipment, wheeled loaders, lubricated systems, excavators, industrial power units, and mobile cranes.

Products
Benefits:

- Prevents ingress of large objects into hydraulic systems
- Lengthens time in between required maintenance intervals, reduces operating costs, and extends overall equipment/machine operational life

Industries
Features:

- Capable of flows up to 500 l/min (132 gpm).
- Operating temperature range: -30 to +90°C (-22 to +194°F)
- Optional 0.17 bar bypass valve available

Solutions
Connections: threads: G½, G¾, G1, G1½, G2, G2½, G3"

Where to Buy For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
