

Low Pressure In-Line Filter - SF1040 Series

Part #: SF1040205QVNHR32C1S02



The SF1040 is a low pressure Multi-purpose filter for gas and high flow fluid systems. Suitable for flows up to 1400 l/min and pressures up to 10 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Flow Rate:	0 to 800 l/min	Pressure Rating:	10 bar
Flow Rate:	1400 L/min	Filter Element Type:	05Q Microglass
Bypass Valve Pressure Rating:	2.0 bar	Housing Material:	Steel
Seal Material:	Fluorelastomer	Indicator Type:	No indicator block, ports plugged
Mounting Type:	Inline	Operating Temperature:	-20 / +120 °C
Connection Type:	2"SAE - 3000 psi	Indicator Pressure Setting:	No indicator
Micron Rating:	5 µm	Options:	With DNV certificate and NR13 documents

[Safety Warning](#)

Item Information

Items marked with an asterisk * in the drop-down menus are standard choices.

The SF1040 series is a low pressure Multi-purpose filter for gas and high flow hydraulic, lubrication and fuel oil systems. It has a strong welded steel construction housing featuring DN80 or DN100 connections. The SF1040 has several options available including PED 3 classified versions for gas applications, a secondary safety element to secure filtration even in by pass situations, and a range of differential pressure indicators for accurate operation control.

Applications:

- Lubricating oil filter for industrial systems

- Gas fine filter for combustion engines
- Fuel oil filter for high flow systems
- Large in line low-pressure filter for hydraulic systems

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

