

Products

Support

Industries oducts / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / Tanktop Mounted S... / SRL1210QLBPGG161

Services

Tanktop Mounted Suction and Return Filter - SR Series

wRard t#BSRL1210QLBPGG161





The SR series filters are capable of feeding filtered oil under positive pressure to the suction side of the boost pump filtering both open and closed loop oil systems through one

View Series Page

Share / Email

Print

Pr

Technical Specifications

Flow Rate: 0 to 125 l/min Brand:

Hydraulic & Industrial Process Filtration Division EMEA Division:

Bypass Valve

Pressure Rating:

Return G1", Suction G3/4" Connection Type:

Industry: Construction, Agriculture, Materials Handling

Filter Element 10QL Ecoglass

Type:

Road Sweepers, Road Rollers, Fork Lift Trucks, Loading Application: Shovels, Telescopic Handlers, Dump Trucks, Skid Steers, Agricultural Harvesting Machines, Mini Excavators

Indicator Type: No indicator, port plugged R Technology: Filtration, Hydraulics Product Type: Hydraulic Filters Options: Standard

⚠ Safety Warning

Product Style: Tanktop Mounted Suction and Return Filter

Product Series: SR Series For Fluid Type: Hvdraulic Oil Operating 10 bar, 150 psi Pressure:

Operating

-30 to +110 °C, -22 to +230 °F Temperature:

Mounting Type: Tank Mounted Housing Material: Aluminium

Specifications Degree of filtration determined by multipass test

Met: according to ISO 16889

Micron Rating: Indicator Pressure No indicator bar

Setting:

Nitrile Seal Material:

Item Information

The SR series filters are capable of filtering both open and closed loop oil circuits through one filter. SR1 and SR2 are capable of feeding filtered oil under positive pressure to the suction side of the boost pump, filtering both open and closed loop oil systems through one filter.

Features and Benefits

- Compact design Less space required for improved flexibility during system design
- Bypass valve mounted in series with back-pressure valve Ensures pressurisation of filtered oil for hydrostatic drive resulting in lower risk of pump cavitation and oil foaming

- Safeguards the use of genuine parts for guaranteed quality of filtration

n filter head – Strainer filters all bypassed fluid by using a system-matched degree of filtration for improved protection of system

Home Home Initial level of customisation – Dedicated system-matched solutions can easily be made available for improved integration of filter in system combined with lower initial system costs Products

- Quick response bypass with low hysteresis Reduction of bypass period and only a small part of the total flow is bypassing the element <u>Support</u>
- $\,$ $\,$ Standard or customised funnel Oil enters the tank under the oil level for significant reduction in oil foaming $\underline{\text{Industries}}$
- Multiple ports availability More compact solutions can be realised, the use of manifold blocks can be avoided, easy to integrate with cooler Services

Sclation Drawings + Files Where to Buy	+
Related Documents	+



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

+ Company Information
+ Global Operations
+ Help & Support
+ Follow Us:

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS



<u>Home</u>

Products

<u>Support</u>

Industries

<u>Services</u>

Solutions

Where to Buy