

Home

Products

Support

Industries

Services

Solutions

Where to Buy

Home / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / Tanktop Mounted R... / STF1020QLBP2HLC24G

Tanktop Mounted Return Line Filter - STF Series

Part #: STF1020QLBP2HLC24G







The STF Series return line filters are designed for situations where the use of aluminium is restricted in applications such as marine and industrial.

Max. flow 500 l/min - Max. pressure 10 bar.

View Series Page

Share / Email

Print

Pr

Technical Specifications

Flow Rate: 0 to 650 l/min Mounting Type: Tank Mounted Bypass Valve Pressure Rating: 2.0 bar Pressure Rating: 10 bar Connection Type: 1½"SAE-3000 + G1

Filter Element Type: 20QL Ecoglass Flow Rate: 500 L/min

▲ Safety Warning

Housing Material: Cast Iron (GGG40) Micron Rating: 20 µm **Operating Temperature:** -40 / +100 °C

Indicator Type: No indicator, ports plugged L+R Options: Diffuser type T, Air tight

Seal Material: Nitrile

Item Information

Items marked with an asterisk * in the drop-down menus are standard choices.

The Parker Filtration STF Series Return Line Filters STF Tank top mounted return filters feature pre-filtration by means of a magnet column and a bypass with low hysteresis.

Thanks to the "In-to-Out" filtration principle, contaminated oil cannot leak back into the system.

The STF filter has a casted iron filter head assembly, making it ideal for marine and industrial applications were the use of aluminium is restricted. The filter head with multiple ports, capable of handling flow up to 500 l/min at 10 bar working pressure, represents an easy and effective way of integrating return line filtration with power packs.

Optional airtight diffusers are standard to avoid air ingress in the return line.

Product Features:

- 'In-to-out' filtration design means contaminated oil cannot leak back into the system.
- · Magnetic pre-filtration.
- · Cast iron filter head assembly
- · Multiple port configuration.
- Flows up to 500 L/min.
- 10 bar maximum working pressure.
- Optional airtight diffusers.
- · LEIF® low environmental impact filter elements as standard.

Typical Applications

- Marine power pack
- Steel mills
- Mining equipment
- Drilling equipment

CAD Drawings + Files + Related Documents +



Parker Sales Company UK

<u>psc.uk.webform@support.parker.com</u> +44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us:

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS