

Tanktop Mounted Return Line Filter - STF Series

Part # STF810QLBS3EGL24G



The STF Series return line filters are designed for situations where the use of aluminium is restricted in applications such as marine and industrial.
Max. flow 500 l/min - Max. pressure 10 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Flow Rate:	0 to 450 l/min	Micron Rating:	10 µm
Mounting Type:	Tank Mounted	Housing Material:	Cast Iron (GGG40)
Bypass Valve Pressure Rating:	1.5 bar	Indicator Type:	Electrical 42V, NC, G1/8
Pressure Rating:	10 bar	Operating Temperature:	-40 / +100 °C
Connection Type:	G1¼ + G1	Options:	Diffuser type T, Air tight
Filter Element Type:	10QL Ecoglass	Seal Material:	Nitrile
Flow Rate:	300 L/min		

[Safety Warning](#)

Item Information

Items marked with an asterisk * in the drop-down menus are standard choices.

The Parker Filtration STF Series Return Line Filters STF Tank top mounted return filters feature pre-filtration by means of a magnet column and a bypass with low hysteresis. Thanks to the "In-to-Out" filtration principle, contaminated oil cannot leak back into the system. The STF filter has a casted iron filter head assembly, making it ideal for marine and industrial applications where the use of aluminium is restricted. The filter head with multiple ports, capable of handling flow up to 500 l/min at 10 bar working pressure, represents an easy and effective way of integrating return line filtration with power packs. Optional airtight diffusers are standard to avoid air ingress in the return line.

Product Features:

- 'In-to-out' filtration design means contaminated oil cannot leak back into the system.
- Magnetic pre-filtration.
- Cast iron filter head assembly
- Multiple port configuration.
- Flows up to 500 L/min.
- 10 bar maximum working pressure.
- Optional airtight diffusers.
- LEIF® low environmental impact filter elements as standard.



- Mining equipment
- Drilling equipment

[Home](#)

[Products](#)
CAD Drawings + Files



[Support](#)

[Industries](#)
Related Documents



[Services](#)

[Solutions](#)

[Where to Buy](#)



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

[+ Company Information](#)

[+ Global Operations](#)

[+ Help & Support](#)

[+ Follow Us :](#)

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
