

[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [Tanktop Mounted R...](#) / TPR210CBP2EG12S

[Where To Buy](#)

Tanktop Mounted Return Line Filter - Tanktopper Series

Part #: TPR210CBP2EG12S



The Tanktopper from Parker is an all-in-one, easy-to-mount return line filter solution featuring an integrated air breather for a compact and cost-effective tank design.

[View Series Page](#) ≡ [Share / Email](#) ↗ [Print](#) 🖨

Technical Specifications

Brand:	Parker	Product Series:	Tanktopper
Flow Rate:	0 to 90 l/min	Indicator Pressure Setting:	No indicator
Bypass Valve Pressure Rating:	1.5 bar	Options:	No Breather, no airguide
Division:	Hydraulic & Industrial Process Filtration Division EMEA	Product Style:	Tanktop Return Line
Industry:	Industrial Manufacturing Equipment	Seal Material:	Nitrile
Connection Type:	G¾"	For Fluid Type:	Hydraulic Oil
Filter Element Type:	10C Cellulose	Operating Pressure:	10 bar, 150 psi
Application:	Fork Lift Trucks, Power Packs, Mini Excavator, Gully-Sucker, Dredging Ships, Mobile Cranes, Refuse Vehicles	Operating Temperature:	-40 to +80 °C, -40 to +176 °F
Technology:	Filtration	Mounting Type:	Tank Mounted
Micron Rating:	10 µm	Housing Material:	Aluminium
Product Type:	Hydraulic Filter	Specifications Met:	Degree of filtration determined by multipass test according to ISO 16889.
Indicator Type:	No indicator, ports plugged L+R		

[Safety Warning](#)

Item Information

The Tanktopper series is a return line filter with an integrated air breather eliminating the use of a separate air breather for a more compact, cost-effective design. The air breather is equipped with a high-quality labyrinth preventing oil leakage for improved efficiency. A second port and dipstick are available so the filler port and level indicator can be integrated into the filter significantly reducing the use of reservoir accessories.

A magnetic prefiltration column removes ferrous particles, even during bypass conditions for improved fluid cleanliness levels and extended element lifetime, while the in-to-out filtration design ensures all captured contamination is retained inside the element preventing recontamination of the system during element changeouts.

Product Features

- Total filtration solution with integrated air breather
- In-to-out filtration plus gauge and switch options



sure of 10 bar



Maximum flow of 650 L/min

Patented *LEIF*® elements safeguard filtration quality

CAD Drawings + Files



Industries

Related Documents



Where to Buy



Americas

USA, Canada, Mexico

cparker@support.parker.com
[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:00800-27-27-5374)

AOG (Aircraft on Ground)

[1-949-851-4357](tel:1-949-851-4357)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)
