



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [Tanktop Mounted R...](#) / TPR210QBP2EG126

[Where To Buy](#)

## Tanktop Mounted Return Line Filter - Tanktopper Series

Part #: TPR210QBP2EG126



The Tanktopper from Parker is an all-in-one, easy-to-mount return line filter solution featuring an integrated air breather for a compact and cost-effective tank design.

[View Series Page](#) ≡ [Share / Email](#) ➔ [Print](#) 🖨

### Technical Specifications

Flow Rate:	0 to 70 l/min	Indicator Pressure Setting:	No indicator
Brand:	Parker	Product Series:	Tanktopper
Bypass Valve		Product Style:	Tanktop Return Line
Pressure Rating:	1.5 bar	Options:	Incl. Dipstick
Division:	Hydraulic & Industrial Process Filtration Division EMEA	For Fluid Type:	Hydraulic Oil
Connection Type:	G $\frac{3}{4}$ "	Seal Material:	Nitrile
Industry:	Industrial Manufacturing Equipment	Operating Pressure:	10 bar, 150 psi
Filter Element Type:	10Q Microglass	Operating Temperature:	-40 to +80 °C, -40 to +176 °F
Application:	Fork Lift Trucks, Power Packs, Mini Excavator, Gully-Sucker, Dredging Ships, Mobile Cranes, Refuse Vehicles	Mounting Type:	Tank Mounted
Micron Rating:	10 µm	Housing Material:	Aluminium
Technology:	Filtration	Specifications Met:	Degree of filtration determined by multipass test according to ISO 16889.
Product Type:	Hydraulic Filter		
Indicator Type:	No indicator, ports plugged L+R		

[Safety Warning](#)


### Item Information

The Tanktopper series is a return line filter with an integrated air breather eliminating the use of a separate air breather for a more compact, cost-effective design. The air breather is equipped with a high-quality labyrinth preventing oil leakage for improved efficiency. A second port and dipstick are available so the filler port and level indicator can be integrated into the filter significantly reducing the use of reservoir accessories.

A magnetic prefiltration column removes ferrous particles, even during bypass conditions for improved fluid cleanliness levels and extended element lifetime, while the in-to-out filtration design ensures all captured contamination is retained inside the element preventing recontamination of the system during element changeouts.

#### Product Features

- Total filtration solution with integrated air breather
- In-to-out filtration plus gauge and switch options

-  Pressure of 10 bar
- Maximum flow of 650 L/min
- Patented *LE/F®* elements safeguard filtration quality

[Home](#)

[Products](#) ▾

[CAD Drawings + Files](#)

[Help & Support](#)



[Industries](#)

[Related Documents](#)

[Where To Buy](#)



#### Americas

USA, Canada, Mexico

[cparker@support.parker.com](mailto:cparker@support.parker.com)  
[1-800-272-7537](tel:1-800-272-7537)

#### Europe

[00800 27 27 5374](tel:00800-27-27-5374)

**AOG (Aircraft on Ground)**

[1-949-851-4357](tel:1-949-851-4357)

+ [Company Information](#)

+ [Global Operations](#)

+ [Help & Support](#)

+ [Follow Us :](#)

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)

---