



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [Tanktop Mounted R...](#) / TPR210QLBG2EG12L

[Where To Buy](#)

# Tanktop Mounted Return Line Filter - Tanktopper Series

Part #: TPR210QLBG2EG12L



The Tanktopper from Parker is an all-in-one, easy-to-mount return line filter solution featuring an integrated air breather for a compact and cost-effective tank design.

[View Series Page](#) ≡ [Share / Email](#) ➔ [Print](#) 🖨

## Technical Specifications

|                               |                                                                                                             |                             |                                                                           |
|-------------------------------|-------------------------------------------------------------------------------------------------------------|-----------------------------|---------------------------------------------------------------------------|
| Flow Rate:                    | 0 to 70 l/min                                                                                               | Indicator Pressure Setting: | 1.2 bar                                                                   |
| Brand:                        | Parker                                                                                                      | Product Series:             | Tanktopper                                                                |
| Bypass Valve Pressure Rating: | 1.5 bar                                                                                                     | Product Style:              | Tanktop Return Line                                                       |
| Division:                     | Hydraulic & Industrial Process Filtration Division EMEA                                                     | Options:                    | Aluminium funnel + magnet                                                 |
| Industry:                     | Industrial Manufacturing Equipment                                                                          | For Fluid Type:             | Hydraulic Oil                                                             |
| Connection Type:              | G¾"                                                                                                         | Seal Material:              | Nitrile                                                                   |
| Filter Element Type:          | 10QL Ecoglass                                                                                               | Operating Pressure:         | 10 bar, 150 psi                                                           |
| Application:                  | Fork Lift Trucks, Power Packs, Mini Excavator, Gully-Sucker, Dredging Ships, Mobile Cranes, Refuse Vehicles | Operating Temperature:      | -40 to +80 °C, -40 to +176 °F                                             |
| Micron Rating:                | 10 µm                                                                                                       | Mounting Type:              | Tank Mounted                                                              |
| Technology:                   | Filtration                                                                                                  | Housing Material:           | Aluminium                                                                 |
| Product Type:                 | Hydraulic Filter                                                                                            | Specifications Met:         | Degree of filtration determined by multipass test according to ISO 16889. |
| Indicator Type:               | Visual, pressure gauge                                                                                      |                             |                                                                           |

[Safety Warning](#)


## Item Information

The Tanktopper series is a return line filter with an integrated air breather eliminating the use of a separate air breather for a more compact, cost-effective design. The air breather is equipped with a high-quality labyrinth preventing oil leakage for improved efficiency. A second port and dipstick are available so the filler port and level indicator can be integrated into the filter significantly reducing the use of reservoir accessories.

A magnetic prefiltration column removes ferrous particles, even during bypass conditions for improved fluid cleanliness levels and extended element lifetime, while the in-to-out filtration design ensures all captured contamination is retained inside the element preventing recontamination of the system during element changeouts.

### Product Features

- Total filtration solution with integrated air breather
- In-to-out filtration plus gauge and switch options

-  Pressure of 10 bar
- Maximum flow of 650 L/min
- Patented *LE/F®* elements safeguard filtration quality

[Home](#)

[Products](#) ▾

[CAD Drawings + Files](#)

[Help & Support](#)



[Industries](#)

[Related Documents](#)

[Where To Buy](#)



#### Americas

USA, Canada, Mexico

[cparker@support.parker.com](mailto:cparker@support.parker.com)  
[1-800-272-7537](tel:1-800-272-7537)

#### Europe

[00800 27 27 5374](tel:00800-27-27-5374)

**AOG (Aircraft on Ground)**

[1-949-851-4357](tel:1-949-851-4357)

+ [Company Information](#)

+ [Global Operations](#)

+ [Help & Support](#)

+ [Follow Us :](#)

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)

---