

 $\bigcirc$  $\blacksquare$ 

Products ~

Help & Support

Industries oducts / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / Tanktop Mounted R... / TPR210QLBS2EG12L

Where To Buy

# Tanktop Mounted Return Line Filter - Tanktopper Series

Part #: TPR210QLBS2EG12L







The Tanktopper from Parker is an all-in-one, easy-to-mount return line filter solution featuring an integrated air breather for a compact and cost-effective tank design.

View Series Page **:** Share / Email **→** Print **-**

### **Technical Specifications**

Flow Rate: 0 to 70 l/min Brand: Parker Bypass Valve 1.5 bar Pressure Rating:

Division: Hydraulic & Industrial Process Filtration Division EMEA

Connection Type:

Industry: Industrial Manufacturing Equipment 10QL Ecoglass

Filter Element Type:

Fork Lift Trucks, Power Packs, Mini Excavator, Gully-Application: Sucker, Dredging Ships, Mobile Cranes, Refuse

Vehicles

Micron Rating: 10 µm Technology: Filtration Hydraulic Filter Product Type: Indicator Type: Electrical 42V, NO

**⚠** Safety Warning

Indicator Pressure

1.2 bar Setting: **Product Series:** Tanktopper Product Style: Tanktop Return Line

Options: Aluminium funnel + magnet For Fluid Type: Hydraulic Oil

Seal Material: Nitrile Operating Pressure: 10 bar, 150 psi

Operating -40 to +80 °C, -40 to +176 °F Temperature:

Mounting Type: Tank Mounted Housing Material: Aluminium

Degree of filtration determined by multipass test Specifications Met: according to ISO 16889.

### **Item Information**

The Tanktopper series is a return line filter with an integrated air breather eliminating the use of a separate air breather for a more compact, costeffective design. The air breather is equipped with a high-quality labyrinth preventing oil leakage for improved efficiency. A second port and dipstick are available so the filler port and level indicator can be integrated into the filter significantly reducing the use of reservoir accessories.

A magnetic prefiltration column removes ferrous particles, even during bypass conditions for improved fluid cleanliness levels and extended element lifetime, while the in-to-out filtration design ensures all captured contamination is retained inside the element preventing recontamination of the system during element changeouts.

#### **Product Features**

- · Total filtration solution with integrated air breather
- · In-to-out filtration plus gauge and switch options

Home imum flow of 650 L/min

 $\underbrace{ \text{Products}}_{\text{Products}} \text{$\text{LEIF}$} \text{$\text{e}$ elements safeguard filtration quality}$ 

## <u>нСАDsDraw</u>ings + Files

+

<u>Industries</u>

Related Documents





#### **Americas**

USA, Canada, Mexico

<u>cparker@support.parker.com</u> 1-800-272-7537

Europe

00800 27 27 5374

AOG (Aircraft on Ground)

1-949-851-4357

+ Company Information
+ Global Operations
+ Help & Support
+ Follow Us:

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS



 $\exists$   $\bigcirc$ 

<u>Home</u>

Products ~

Help & Support

**Industries** 

Where To Buy