

# Tanktop Mounted Return Line Filter - Tanktopper Series

Part #: TPR220QBG2EG12E



The Tanktopper from Parker is an all-in-one, easy-to-mount return line filter solution featuring an integrated air breather for a compact and cost-effective tank design.

[View Series Page](#) [Share / Email](#) [Print](#)

## Technical Specifications

|                               |   |                             |   |
|-------------------------------|---|-----------------------------|---|
| Brand:                        | Parker  | Indicator Pressure Setting: | 1.2 bar   |
| Flow Rate:                    | 0 to 80 l/min   | Product Series:             | Tanktopper  |
| Bypass Valve Pressure Rating: | 1.5 bar   | Options:                    | Incl. Magnet  |
| Division:                     | Hydraulic & Industrial Process Filtration Division EMEA   | Product Style:              | Tanktop Return Line   |
| Industry:                     | Industrial Manufacturing Equipment  | For Fluid Type:             | Hydraulic Oil   |
| Connection Type:              | G¾"   | Seal Material:              | Nitrile   |
| Filter Element Type:          | 20Q Microglass  | Operating Pressure:         | 10 bar, 150 psi   |
| Application:                  | Fork Lift Trucks, Power Packs, Mini Excavator, Gully-Sucker, Dredging Ships, Mobile Cranes, Refuse Vehicles | Operating Temperature:      | -40 to +80 °C, -40 to +176 °F   |
| Technology:                   | Filtration  | Mounting Type:              | Tank Mounted  |
| Micron Rating:                | 20 µm   | Housing Material:           | Aluminium   |
| Product Type:                 | Hydraulic Filter  | Specifications Met:         | Degree of filtration determined by multipass test according to ISO 16889. |
| Indicator Type:               | Visual, pressure gauge  |                             |   |

[Safety Warning](#)

## Item Information

The Tanktopper series is a return line filter with an integrated air breather eliminating the use of a separate air breather for a more compact, cost-effective design. The air breather is equipped with a high-quality labyrinth preventing oil leakage for improved efficiency. A second port and dipstick are available so the filler port and level indicator can be integrated into the filter significantly reducing the use of reservoir accessories.

A magnetic prefiltration column removes ferrous particles, even during bypass conditions for improved fluid cleanliness levels and extended element lifetime, while the in-to-out filtration design ensures all captured contamination is retained inside the element preventing recontamination of the system during element changeouts.

### Product Features

- Total filtration solution with integrated air breather
- In-to-out filtration plus gauge and switch options



ure of 10 bar

• Maximum flow of 650 L/min

• Patented *LEIF*® elements safeguard filtration quality

**CAD Drawings + Files**

[Home](#)  
[Products](#)  
[Help & Support](#)



[Industries](#)

**Related Documents**

[Where To Buy](#)



### Americas

USA, Canada, Mexico

[cparker@support.parker.com](mailto:cparker@support.parker.com)  
[1-800-272-7537](tel:1-800-272-7537)

### Europe

[00800 27 27 5374](tel:00800-27-27-5374)

**AOG (Aircraft on Ground)**

[1-949-851-4357](tel:1-949-851-4357)

---

+ Company Information

---

+ Global Operations

---

+ Help & Support

---

+ Follow Us :

---

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)

---