

Tanktop Mounted Return Line Filter - Tanktopper Series

Part #: TPR520QLBS2EG241



The Tanktopper from Parker is an all-in-one, easy-to-mount return line filter solution featuring an integrated air breather for a compact and cost-effective tank design.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Brand:	Parker	Indicator Pressure Setting:	1.2 bar
Flow Rate:	0 to 140 l/min	Product Series:	Tanktopper
Bypass Valve		Options:	Incl. Magnet
Pressure Rating:	1.5 bar	Product Style:	Tanktop Return Line
Division:	Hydraulic & Industrial Process Filtration Division EMEA	For Fluid Type:	Hydraulic Oil
Industry:	Industrial Manufacturing Equipment	Seal Material:	Nitrile
Connection Type:	G1½"	Operating Pressure:	10 bar, 150 psi
Filter Element Type:	20QL Ecoglass	Operating Temperature:	-40 to +80 °C, -40 to +176 °F
Application:	Fork Lift Trucks, Power Packs, Mini Excavator, Gully-Sucker, Dredging Ships, Mobile Cranes, Refuse Vehicles	Mounting Type:	Tank Mounted
Technology:	Filtration	Housing Material:	Aluminium
Micron Rating:	20 µm	Specifications Met:	Degree of filtration determined by multipass test according to ISO 16889.
Product Type:	Hydraulic Filter		
Indicator Type:	Electrical 42V, NO		

 [Safety Warning](#)

Item Information

The Tanktopper series is a return line filter with an integrated air breather eliminating the use of a separate air breather for a more compact, cost-effective design. The air breather is equipped with a high-quality labyrinth preventing oil leakage for improved efficiency. A second port and dipstick are available so the filler port and level indicator can be integrated into the filter significantly reducing the use of reservoir accessories.

A magnetic prefiltration column removes ferrous particles, even during bypass conditions for improved fluid cleanliness levels and extended element lifetime, while the in-to-out filtration design ensures all captured contamination is retained inside the element preventing recontamination of the system during element changeouts.

Product Features

- Total filtration solution with integrated air breather
- In-to-out filtration plus gauge and switch options
- Maximum pressure of 10 bar
- Maximum flow of 650 L/min
- Patented *LEIF*® elements safeguard filtration quality

CAD Drawings + Files



Related Documents



Americas

USA, Canada, Mexico

cparker@support.parker.com
[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:00800-27-27-5374)

AOG (Aircraft on Ground)

[1-949-851-4357](tel:1-949-851-4357)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

