

[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#) / [Products](#) / [Filters, Collectors, Separators](#) / [Filter Assemblies and Vessels](#) / [Hydraulic Filters](#) / [Tanktop Mounted Return Line Filters](#) / [TTF210QLBP2EG123](#)

[Where To Buy](#)

Tanktop Mounted Return Line Filter - TTF Series

Part #: TTF210QLBP2EG123



The TTF Series features pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Maximum pressure 10 bar. Maximum flow 500 l/min. A second return port is an available option as is a filling port in the filter cover.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

| | | | |
|-------------------------------|--|-------------------------------|------------------------------------|
| Filter Element: | 10QL Ecoglass * | Technology: | Filtration, Hydraulics |
| Flow Capacity (l/min): | 60 | Product Type: | Hydraulic Oil Filters |
| Bypass Valve (bar): | 1,5 * | Indicator Type: | No indicator, port plugged L+R |
| Port Connection Type: | G3/4 * | Options: | Diffuser type T |
| Brand: | Parker | Product Series: | TTF Series |
| Flow Rate: | 0 to 85 l/min | Product Style: | Tanktop Mounted Return Line Filter |
| Bypass Valve Pressure Rating: | 1.5 bar | Seal Material: | Nitrile |
| Division: | Hydraulic & Industrial Process Filtration Division | Bypass Valve Pressure Rating: | 1.5 bar |
| Connection Type: | EMEA | Operating Pressure: | 10 bar, 150 psi |
| Industry: | Trucks and Buses, Materials Handling, Construction | Operating Temperature: | -40 to 100 °C |
| Filter Element Type: | 10QL Ecoglass | Filter Element Type: | 10QL Ecoglass |
| Application: | Refuse Trucks, Mobile Cranes, Power Packs, Wheel Loaders, Drilling Equipment | Mounting Type: | Tanktop Mounted |
| Micron Rating: | 10 µm | Indicator Pressure Setting: | No indicator |

[Safety Warning](#)

Item Information

Parker TTF tank top mounted return line filters feature pre-filtration by means of a magnet column and a quick response bypass with low hysteresis. Thanks to the "In-to-Out" filter principle, contaminated oil cannot leak back into the system during element change.

TTF filters are available in formats capable of handling flow rates up to 500 l/min. They can operate up to a maximum working pressure of 10 bar. Options include a filling port in the filter cover, a second return port and customised diffusers can be specified.

Features and Benefits

- 10 bar rated filter can be utilised for severe return line applications for reduced downtime due to premature filter failures



elements safeguard filtration quality



[Home](#) Magnetic pre-filtration removes ferrous particles, even during bypass conditions for improved cleanliness levels and extended element life time

[Products](#) In-line-out filtration means captured contamination is retained inside the element preventing recontamination of the filter

[Help & Support](#) Quick response bypass with low hysteresis for improved system protection.

[CAD Drawings + Files](#)



[Where To Buy](#)

[Related Documents](#)



Americas

USA, Canada, Mexico

cparker@support.parker.com
[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:00800-27-27-5374)

AOG (Aircraft on Ground)

[1-949-851-4357](tel:1-949-851-4357)

[+ Company Information](#)

[+ Global Operations](#)


[+ Help & Support](#)

[+ Follow Us :](#)

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)
